



AMPLIFIERS/ LOW IMPEDANCE (8/4/2Ω)/ eGPA2-150

Applications

- Clubs
- Theme restaurants
- Discos
- Leisure centres
- Cinemas and theatre
- Educational centres
- Boardrooms and conference halls
- Sports centres
- Mobile outdoor applications

Stereo Amplifier

ECLER eGPA2-150 is a stereo, 2x150 W RMS @ 4 Ω, high efficiency amplifier (class D). Auto stand-by function and fanless design, 100% silent. Thermal and overload protections. Anti-clip system.



Key Features

- 2 analogue audio inputs x 2 powered audio outputs
- Euroblock input and output connectors
- High efficiency, auto standby function and convection cooling (fanless, 100% silent)
- BRIDGE mode ready
- Thermal protection
- Overload protection
- Anti-clip system

Main Technical Specifications	POWER 20-20kHz 1% THD				
	1 Channel @ 4Ω (RMS)	140 W			
	1 Channel @ 8Ω (RMS)	70 W			
	All Channels @ 4Ω (RMS)	140 W			
	2 Bridged ch. @ 8Ω (RMS)	280 W			
	Frequency response (-1dB, -3dB)	20Hz - 25kHz			
	Dimensions / weight	H: 440 mm	L: 44 mm	W: 161 mm	2.60 Kg

Accessories

- N/A