



AMPLIFIERS/

LOW IMPEDANCE (8/4/2Ω)/

eGPA4-150

Applications

- Clubs
- Theme restaurants
- Discos
- Leisure centres
- Cinemas and theatre
- Educational centres
- Boardrooms and conference halls
- Sports centres
- Mobile outdoor applications

Multichannel Amplifier

ECLER eGPA4-150 is a 4x150 W RMS @ 4 Ω, high efficiency multichannel amplifier (class D). Auto stand-by function and fanless design, 100% silent. Thermal and overload protections. Anti-clip system.



Key Features

- 4 analogue audio inputs x 4 powered audio outputs
- Euroblock input and output connectors
- High efficiency, auto standby function and convection cooling (fanless, 100% silent)
- BRIDGE mode ready
- Thermal protection
- Overload protection
- Anti-clip system

Main Technical Specifications	POWER 20-20kHz 1% THD			
	1 Channel @ 4Ω (RMS)	140 W		
	1 Channel @ 8Ω (RMS)	70 W		
	All Channels @ 4Ω (RMS)	140 W		
	2 Bridged ch. @ 8Ω (RMS)	280 W		
	Frequency response (-1dB, -3dB)	20Hz - 25kHz		
	Dimensions / weight	H: 440 mm	L: 44 mm	W: 221 mm

Accessories

- N/A