


## ARQIS112

### CABINET LOUDSPEAKERS

#### *Architectural Loudspeaker Cabinet*



### PRODUCT OVERVIEW

ECLER ARQIS 112 is a wooden loudspeaker cabinet with a compact format, stylish aesthetics, excellent sound quality and long term reliability, featuring 340 WRMS @ 8 ohm, 12" woofer and 1,4" HF Compression Driver. 35 mm mount socket and 8 x M10 rigging points, allowing for horizontal or vertical mounting options (80°x40° dispersion pattern). It has been specifically designed to fulfil permanent installation requirements where a perfect balance between sound performance and architectural/interior's design matching is a must.

### KEY FEATURES


- Full range, 2-way architectural loudspeaker
- 340 WRMS @ 8 ohm
- 1 x 12" low frequency woofer
- 1,4" high frequency compression driver
- Double INPUT/STACK connector, Euroblock + Speakon® type, with security attachment screws to avoid accidental disconnection
- 35 mm mount socket, compatible with SR10 / SR12 wall brackets (not included)
- 8 x M10 cabinet flying points.
- Metal safety sling included, to avoid drops in case of accidental detachment from the wall surface
- Available in black finish

### APPLICATIONS


- Shopping malls
- Sports centres
- Theatres / auditoriums
- Conference rooms
- A/V presentations
- Corporate rooms
- Perimeter reinforcement in clubs
- Cafés
- Restaurants
- Theme parks

POLAR DIAGRAMS


HORIZONTAL



VERTICAL



## FREQUENCY RESPONSE



## TECHNICAL DATA

<b>Ways</b>	2
<b>Nominal low impedance</b>	8Ω
<b>Max RMS power</b>	340 WRMS
<b>Program power</b>	680 WRMS
<b>Efficiency SPL 1W 1m</b>	97dB
<b>Sound pressure (Max W/1m)</b>	122dB
<b>Frequency response (±3dB)</b>	60Hz-18kHz
<b>Frequency range (-10dB)</b>	50Hz-19kHz
<b>Cross-over frequency</b>	2.5kHz
<b>Dispersion (HxV)</b>	80°x40°
<b>Driver LF/MF</b>	12"
<b>Driver HF</b>	Tweeter 1.4
<b>Connection</b>	1 Euroblock + 1 Speakon®
<b>Dimensions (WxHxD)</b>	416x565x352mm
<b>Weight</b>	20.0kg/pcs