

DIGITAL PROJECTOR | MW705



Features


- WXGA (1280x800) resolution
- 4,000 ANSI lumens
- Dual HDMI, MHL x 1
- H + V keystone image adjustment
- Optional wireless presentation on the go



Specifications

Projection System	DLP®
Native Resolution	WXGA (1280x800)
Brightness	4000 ANSI Lumen
Contrast Ratio	13000:1
Display Color	1.07 Billion Colors
Lens	F=2.56~2.68, f=22.04~24.14mm
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)
Throw Ratio	1.55~1.7(87"@2.9m)
Image Size	60" ~ 180"
Zoom Ratio	1.1x
Lamp Type	240W
Lamp (Normal/Eco/SmartEco Mode)	2500/4000/6000/7500(80%~30%) hours
Keystone Adjustment	2D, Vertical & Horizontal ± 40 degrees; Auto vertical keystone ± 30 degrees
Projection Offset	Vertical: 100% ±5%
Resolution Support	VGA(640 x 480) to UXGA (1600 x 1200)
Horizontal Frequency	15K-102KHz
Vertical Scan Rate	23-120Hz
Compatibility	HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p Video Compatibility: NTSC, PAL, SECAM 3D Compatibility: Frame Sequential: Up to 60Hz 720p Frame Packing: Up to 24 Hz 1080p Side by Side: Up to 24Hz 1080p Top Bottom: Up to 60Hz 1080p
Interface	Computer in (D-sub 15pin) x 1 (integrate with component) HDMI x 2 (HDMI with MHL2.0 x1, HDMI x 1) MHL x 1 (HDMI with MHL2.0) Monitor out x 1 Composite Video in (RCA) x 1 S-Video in x 1 Audio in (Mini Jack) x 1 Audio in (L/R) x 1 Audio out (Mini Jack) x 1 Speaker 2W x 1 USB (Type A) x 1 (1.5A power supply) RS232 (DB-9pin) x 1 IR Receiver x 2 (Front+Top)
Dimensions (WxHxD)	11.8" x 3.4" x 9.4" / 300 x 88 x 240 mm (feet included)
Weight	6.6 lbs / 3 Kg
Power Supply	AC100 to 240V, TBD A, 50 to 60 Hz
Power Consumption	Typical 350W, Standby <0.5W
Power Management Function	Automatic power off after 20 minutes without a display source
Audible Noise	31/28 dBA (Normal/Economic mode)
Languages	(28 Languages)
Picture Mode	**Dynamic / Presentation / sRGB / Cinema / (3D) / User 1 / User 2
Accessories (Standard)	Carry bag, Power Cord, Remote Control w Battery, VGA cable, User Manual CD, QSG Lens Cover, Warranty Card
Accessories (Optional)	Spare Lamp Kit P/N: 5J.JEC05.001 Ceiling mount kit P/N: 5J.JAM10.001 3D Glasses P/N: 5J.J9H25.001 QCast Dongle QP01 P/N: 5J.JCK28.A01
UPC / Part #	8400460-3317-0 / 9H.JEC77.13A
Limited Warranty	1 year parts and labor / 1 year or 2,000 hours lamp life

Input and Output Terminals



- | | |
|-----------------------------|------------------------------|
| 1 USB (Type mini-B) | 6 Audio In & Out (Mini Jack) |
| 2 RS232 (DB-9pin) | 7 S-Video in |
| 3 HDMI | 8 Audio L/R in (RCA) |
| 4 USB (Type A) | 9 Monitor out |
| 5 Computer in (D-sub 15pin) | 10 Composite Video in (RCA) |
| | 11 HDMI / MHL |

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.



BenQ America Corp.
www.BenQ.us

BenQ is a registered trademark of BenQ Corp. All rights reserved. Product names, logos, brands, and other trademarks featured or referred to in this material are the property of their respective trademark holders. Specifications subject to change without notice.

MW705 100715_BQus

BenQ

Because it matters