



SPK-CC444

2 Closed-Back Ceiling Mount Speakers



The **SPK-CC444** is a pair of two-way speakers designed to be mounted in the ceiling. It has a closed back design with a 4 inch metal can and aluminum grilles.

- Type - 2-way ceiling speaker with metal closed back can and transformer.
- Woofer - 4 inch polypropylene cone woofer.
- Tweeter - 0.5 inch PEI tweeter.
- Impedance - 8Ω.
- Metal Back Can - 4 inches deep.
- Transformer - 4Ω and 70 volt and 100 volt.
- Power Selector - five-position tab selector behind-the-grille.
- Frequency Response - 20Hz – 20kHz.
- Sensitivity - (SPL) 88dB (1 watt @ 1 meter with 1kHz).
- Recommended Power - RMS 30W, 90W max.
- Grille - Aluminum grilles with UV treatment compliance.
- Size - External diameter 21cm (8.27 inches), mounting depth 14.3cm (5.63 inches), cutout diameter 18.1cm (7.13 inches).
- Package - 2 speakers (1 pair), ceiling mounting kit (C-ring & V-rail kit), template and user manual.
- Weight Per Single Speaker - 1.9kg (4.18lbs) approx.
- Shipping Weight (Pair) - 6.8kg (14.97lbs) approx.



SPK-CC444

FEATURES

- **Type** - 2-way ceiling speaker with metal closed back can and transformer.
- **Woofers** - 4 inch polypropylene cone woofer.
- **Tweeter** - 0.5 inch PEI tweeter.
- **Impedance** - 8Ω.
- **Metal Back Can** - 4 inches deep.
- **Transformer** - 4Ω and 70 volt and 100 volt.
- **Power Selector** - five-position tab selector behind-the-grille.
- **Frequency Response** - 20Hz - 20kHz.
- **Sensitivity** - (SPL) 88dB (1 watt @ 1 meter with 1kHz).
- **Recommended Power** - RMS 30W, 90W max.
- **Grille** - Aluminum grilles with UV treatment compliance.
- **Size** - External diameter 21cm (8.27 inches), mounting depth 14.3cm (5.63 inches), cutout diameter 18.1cm (7.13 inches).
- **Package** - 2 speakers (1 pair), ceiling mounting kit (C-ring & V-rail kit), template and user manual.
- **Weight Per Single Speaker** - 1.9kg (4.18lbs) approx.
- **Shipping Weight (Pair)** - 6.8kg (14.97lbs) approx.