

DS346

Bright projection

- Bright projection 3000 ANSI lumens
- SVGA resolution, 18,000:1 contrast ratio, HDMI input
- Low ownership costs up to 10,000 hours² lamp life
- Lightweight and portable













DS346

Simple to connect to with HDMI connectivity the DS346 is ideal for use in a meeting room or classroom. The bright 3000L with 18,000:1 contrast allows you to project bright, crystal clear images with superb colours using DLP®, BrilliantColor™ and Dynamic Eco+ technology. The DS346 also provides you with energy and cost saving features with an incredible lamp life of up to 10,000 hours. It also incorporates a built in speaker, Full 3D technology and optional wireless capabilities allowing you to present wirelessly from a PC or mobile device with ease. Installed or on the move the versatile DS346 is the perfect projector for all your display needs.


Green Solutions



Eco⁺ technology from Optoma increases our commitment to reducing the impact we all make on the environment

Dynamic Mode

Saving energy saves money! Dynamic Mode reduces the power consumption to as little as 30%. This intelligent feature can more than double your expected lamp life, lowering the total cost of ownership and reducing maintenance.



Eco AV Mute

Stay in control of your presentation with the Eco AV mute feature. Direct your audience's attention away from the screen by blanking the image when no longer needed. This also instantly reduces the power consumption to 25%, further prolonging the life of your lamp.



Eco AV mute off 100% power consumption

Eco AV mute on 25% power consumption

Rapid Off

It takes less than 10 seconds for the projector to power up and shutdown, saving both time and energy.

Quick Resume

Save time by not waiting for the projector to cool down before it can power up again. If the projector is accidentally turned off, this feature allows the projector to be instantly powered on again, if selected within a period of 100 seconds.



Full 3D

Using the inherent speed of DLP technology, The Optoma DS346. Full 3D projector can display true 3D content form any 3D display device, such as 3D Blu-ray, PS3, Xbox and Sky3D.

Audio Performance

Built-in 2W speaker offers excellent audio support. The DS346 is easy to set up without the need for costly external speakers




Brightness Where It Matters

Room lighting can be unpredictable for the business traveller; you never know what to expect. The DS346 has a powerful lamp producing 3000 ANSI Lumens, so you can be sure your presentation will be bright and clear.



Cost Saving – Long Lamp Life

Reduce the number of lamp changes with lamp life of up to 10,000 hours² using the Education Cycle.



Clear, Focused Images

Produce a stunning 18,000:1 contrast ratio for pin sharp graphics and crystal clear text using the unique Dynamic mode feature.

Combined with DarkChip3 technology for Texas Instruments, Dynamic mode automatically adjusts the lamp output, based on the brightness information of each frame; to create a stunning high contrast ratio. Bright scenes are crisp and clear, while dark scenes remain detailed with deep blacks which gives exceptional light and shade detail.





2000:1 Contrast Ratio

18,000:1 Contrast Ratio

Digital Connectivity

Simple and easy – connect using a HDMI cable for a digital audio and video connection to your projector giving you a clear projected image with sound.



Wireless Presenting (optional extra)

Making presentations couldn't be easier using the optional wireless features of the DS346. Using the Wireless Adapter you can connect and display presentations and video material wirelessly from a laptop, PC or mobile device.





We know that improving our products is the best way to reduce our impact on the environment. That's why at Optoma we design our products to have a long usable life, use fewer materials, ship with the minimum packaging and be free of all possible toxic substances. Naturally, energy efficiency and being recyclable are built in at the design stage. With each new product, we strive towards minimising our environmental impact.


DS346 Specification

Display Technology	Single 0.55" SVGA DC3 DMD chip DLP® Technology by Texas Instruments
Native Resolution	SVGA 800 x 600
Brightness ¹ (Bright Mode)	3000 ANSI Lumens
Contrast	18,000:1
Lamp Life ² Dynamic/Eco/Bright	6500/6000/5000 (hrs)
Throw Ratio	1.95 - 2.15:1
Zoom Type	1.1x Manual
I/O Connectors	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB Service
Speaker	2
Audio	2W
Keystone Correction	± 40° Vertical
Weight (kg)	2.35
Dimensions (W x D x H) (mm)	314.6 x 223.6 x 101.7
Aspect Ratio	4:3 Native, 16:9 Compatible
Offset	115%
Projection Screen Size	0.70 - 7.62m (22.9" - 300") Diagonal 4:3
Projection Distance	1.2 - 12 metres
Projection Lens	F/2.41~2.55; f=21.8~23.98mm, 1.1x Manual Zoom
Uniformity	80%
Maximum Resolution	UXGA 1600 x 1200
Computer Compatibility	UXGA, SXGA, XGA, SVGA, VGA, Mac
Video Compatibility	PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(24/50/60Hz)
3D Support	The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.
3D Compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D Viewing	Requires the Optoma DLP-Link shutterglasses - available separately.
Horizontal Scan Rate	15.3 - 91.1kHz
Vertical Scan Rate	24 - 85Hz
Displayable Colours	1073.4 Million
Noise Level (Eco mode)	29dB
Power Supply	100-240V, 50-60Hz
Power Consumption	225W BRIGHT mode < 0.5W Standby mode, 191W Eco mode < 0.5W Standby mode
Lamp Type	190W
Operating Conditions	5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m
Security	Security Bar, Kensington Lock, Password Protection
On Screen Display	19 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish, Romanian, Farsi and Arabic.
Remote Control	Card style remote with direct source selecting
Standard Accessories	AC Power Cord, VGA Cable, Infra Red Remote Control with Batteries, Quick Start Card, CD User Manual, Warranty Card
Optional Accessories	Ceiling Mount Kit, WPS
Optional Wireless	Да
Warranty	2 Years
RoHS	Compliant
Features	Eco+, Up to 10,000 hours lamp life - Education Cycle

Навигация с помощью пульта ДУ

Пульт ДУ DS346

- **1.** Вкл./Выкл.
- 2. Источник
- 3. VGA 1 / VGA 2
- 4. HDMI
- **5.** Формат (соотношение сторон)
- 6. Навигация вверх / Трапеция +
- 7. Навигация вправо / Громкость +
- **8.** Ввод
- **9.** Зум
- **10.** Навигация вниз / Трапеция -
- **11.** Лампа
- **12.** Mute
- 13. AV Mute
- **14.** Меню
- **15.** Навигация влево / Громкость -
- **16.** 3D
- **17.** Видео / S-Video
- **18.** Пересинхронизация (ReSync)



Разъёмы DS346

- 1. S-Video
- **2.** VGA-выход
- **3.** VGA 1
- 4. VGA 2
- 5. Видео
- 6. Аудиовход 2
- 7. Заглушка Security Bar
- 8. Аудиовыход
- 9. Аудиовход 1
- **10.** RS232 9-пин
- **11.** USB (сервис / мышь)
- **12.** HDMI
- 13. Питание
- 14. Замок Kensington Lock

Широкий набор коммутационных интерфейсов



Таблица проекционных расстояний DS346 (соотношение сторон 4:3)									
Проекционное расстояние (м)	Макс. размер по горизонтали (м)	Мин. размер по горизонтали (м)	Макс. размер по вертикали (м)	Мин. размер по вертикали (м)	Макс. размер по диагонали (м)	Макс. размер по диагонали (дюймы)	Макс. сдвиг (Offset) (м)		
1.20	0.62	0.56	0.46	0.42	0.77	30.31	0.07		
2.00	1.03	0.93	0.77	0.70	1.28	50.52	0.12		
2.50	1.28	1.16	0.96	0.87	1.60	63.15	0.14		
3.00	1.54	1.40	1.16	1.05	1.92	75.78	0.17		
4.00	2.05	1.86	1.54	1.40	2.57	101.04	0.23		
5.00	2.56	2.33	1.93	1.75	3.21	126.30	0.29		
6.00	3.08	2.79	2.31	2.10	3.85	151.56	0.35		
7.00	3.59	3.26	2.70	2.45	4.49	176.82	0.40		
8.00	4.10	3.72	3.08	2.80	5.13	202.08	0.46		
9.00	4.62	4.19	3.47	3.15	5.77	227.34	0.52		
10.00	5.13	4.65	3.86	3.50	6.42	252.60	0.58		
11.00	5.64	5.12	4.24	3.85	7.06	277.86	0.64		
12.00	6.15	5.58	4.63	4.20	7.70	303.12	0.69		

Для ознакомительных целей

DS346 также поддерживает формат 16:9, при котором параметры изображения, экрана и сдвига будут отличаться от вышеприведённых.



Optoma Europe Ltd.

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ www.optoma.co.uk

¹Brightness and lamp lifetime will vary depending on the selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will decrease over the lamp lifetime. ²Typical lamp life achieved through testing and will vary according to operational use and environmental conditions. 10,000 hours lamp life is based on a daily cycle that reflects projector usage in a typical education environment. Details of this cycle are available on request. ³Optoma guarantees that in normal use, Optoma DLP® colour quality will be indistinguishable from when new. Exclusions: (a) Guarantee is voided if the projector is subject to damage through misuse. (b) Guarantee may be void in industrial or commercial entertainment environments where dust or smoke is excessive (c) Guarantee will not apply if lamp brightness is below 50% due to wear or if the projector is not working due to other faults. (d) Over time worn lamps within all projector types will show a slight colour variance. Copyright © 2013, Optoma Europe Ltd. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. DLP®, BrilliantColor™ and the DLP logo are registered trademarks of Texas Instruments. All images of products are for representation purposes only. Whilst every care is taken to provide accurate images of our products, actual products may differ slightly. Some product images may have been digitally altered by us to add an Optoma logo to the front panel. Optoma reserves the right to amend or alter actual product, product specifications or product images without notice. Some images may be simulated.

21/01/2017 19:48