HCS-4390N/10 Wireless Voting Unit



Technical Specifications

Mechanical

Dimensions (h x w x d)	29 × 183 × 51 mm
Weight	0.2 kç
Color	Gray (PANTONE 424C

Ordering Information

HCS-4390N/10 Wireless Voting Unit (portable, 10 voting keys, LCD display, gray)

Features

- Portable, stylish and ergonomic design
- Wireless digital communication, adopting multilevel error correction and encrypted coding for high confidentiality and low error rate
- Voting unit will upload data on its time slot, this communication type is faster than roll polling. It takes about 1 second for 100 voting units uploading data
- When powered on, voting unit will search RF channel and join in the eligible RF channel automatically
- RF transceiving range: 100 m (frequency optional)
- Max. system capacity: 1200 wireless voting units
- 10 voting keys (0~9), "← " (confirm) key, "C" (cancel) key
- Multiform voting in combination with the corresponding software modules:
 - ♦ For/Against
 - Parliamentary: YES/NO/ABSTAIN
 - ◆ Multi-choice: 1~N
 - Audience response: 0/25/50/75/100
 - Score: 0~100
 - Appraisal:
 - satisfied (Four keys voting:

perfectly satisfied/satisfied/basically satisfied/unsatisfied)

(Three keys voting:

satisfied/basically satisfied/unsatisfied)

(Two keys voting: satisfied/unsatisfied)

- Qualified (four/three/two keys voting)
- Competent (four/three/two keys voting)
- Large LCD for displaying voting and sign-in information, easy to use
- Screen backlight can be turned on/off by software
- Key-press sign-in
- Two alkaline batteries (AA battery) for continuous using not less than 120 hours