SURFIR[®]





SURFiR Companion Remote

The SURFIR companion remote represents a revolutionary new concept in control - allow users to incorporate Apple® or Android[®] devices as the main graphical interface for their control system, while adding the convenience of hard buttons for tactile control. This eliminates the numerous screen swipes needed for control tasks that require frequent interaction such as channel changes, DVR control or volume adjustments. The SURFiR allows the user to enjoy the other benefits of their smart phone or tablet device: checking email, reading news feeds, accessing social media apps, etc. To further enhance the experience for the user, the SURFiR can track which electronic device is being controlled by the RTiPanel app and automatically controls the same. Powerful and intuitive control in an inexpensive package everything you desire in a companion remote.

Key Features

- Provides a companion remote for use with the RTiPanel and Virtual Panel apps.
- . Tracks page changes to stay in sync with one or more apps.
- Dual RF transmission capability uses 433MHz and 2.4GHz (utilizing Zigbee® technology).
- · Remote finder beeper allows user to easily locate SURFIR by pressing a button on their smart phone or tablet.
- · Ergonomic design permits effortless, one-handed operation.
- · Completely customizable and programmable.
- · Security screw on battery door for hotel applications.
- · Inexpensive and requires no direct programming.
- · Includes eight buttons that can be custom labeled.
- Select between 433MHz and 2.4GHz RF operation (See Notes pg 2).
- · Works with any XP series control processor.
- · Battery low indicator.
- Uses 4 AAA batteries.



www.rticorp.com

It's Under Control

Specifications

Power	4 AAA Alkaline batteries
Power Management	Automatic On/Off
Radio Frequency Control Rang	e Up to 100 feet (30.5 meters)
Radio Frequency Carrier	802.15.4 @ 2.4Ghz (Zigbee [®] technology) & 433MHz
Operating Temperature	+32°F to +122°F (0°C to +50°C)
Operating Humidity	
Standby Time	
Total System Memory	
Device Capability Total numb	per of devices determined in control app (ex. RTiPanel)
Macro Capability	All programming stored in RTI XP control processor
	Macro capability on every button
Dimensions (L x W x D)	
Enclosure	High-impact molded ABS plastic
Weight	8.0 oz. (228g) with batteries
Warranty	One Year (Parts & Labor) / 90 days on the battery

All specifications subject to change without notice.

NOTES:

Does NOT have infrared control capability.

• Requires XP series control processor.

• Requires an RM-433 antenna, ZM-24 2.4GHz transceiver module or an RTI control processor with an integrated antenna.

* When used with an XP-3 control processor, 2.4GHz Zigbee RF must be used. 433MHz RF is NOT supported with XP-3 via the RM-433.



Remote Technologies Incorporated 5775 12th Avenue East, Suite 180, Shakopee, MN 55379 PH: (952) 253-3100 • Website: www.rticorp.com

RTI User Interfaces

RTiPanel	Mobile Software Interface (App)
Virtual Panel	PC Software Interface (App)
SURFIR	Companion Remote Control
T1-B+	Remote Control
T2i	Remote Control
T2x	Remote Control
T3x	Remote Control
RKM-1+	In-Wall Audio Distribution Keypad
RK1+	2-4-8 Button In-Wall Keypad
KX2	2.8 inch In-Wall Touchpanel Keypad
KX3	3.5 inch In-Wall Touchpanel Keypad
KX7	7 inch In-Wall Touchpanel
CX7	Countertop/Under-Cabinet Touchpanel



RTI Control Accessories

RP-4	RF Control Processor
XP-3	Advanced Control Processor
XP-6	Advanced Control Processor
XP-8s	Advanced Control Processor
RM433	433MHz RF Antenna
ZM24	2.4GHz Zigbee Transceiver
CB-8	Touchpanel Connecting Block
CM-232	RS-232 Communication Module
CPB-1	Control Port Connecting Block
ECB-5	IR Connecting Block
ESC-2	Ethernet to Serial Converter
IPE-4	IR Port Expander
PCM-4	Port Control Module
RCM-4	Relay Control Module
vIRsa Mouse	IR Emitter



RTI Audio Distribution

AD-4x	Distributed Audio System
AD-8x	Distributed Audio System
CP-450	4 Channel Amplifier
CP-1650	16 Channel Amplifier

