

HCS-3643NCTE Voting Unit



Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 3 voting keys
- Controls voting start and stop

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - Pass-rate setup, voting result calculated automatically
 - Voting result calculated according to predefined or present attendance
 - ◆ Rating
- Controls voting start and stop
- Key-press sign-in
- Automatic detection

Interconnections

- 1.5 m cable with 6P-DIN plug
- 0.6 m cable with 6P-DIN socket

Technical Specifications

Mechanical

Mounting.....Flush-mounting
 Dimensions (h x w x d) (w/o stem microphone)....83 x 111 x 41 mm
 Weight.....93 g
 Color.....Silver/Charcoal gray

Ordering Information

HCS-3643NCTE.....Economical Voting System Chairman Unit
 (flush-mounting, 3 voting keys, silver)
 HCS-3643NCTE_G.....Economical Voting System Chairman Unit
 (flush-mounting, 3 voting keys, charcoal gray)

HCS-3643NDTE Voting Unit



Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 3 voting keys

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - Pass-rate setup, voting result calculated automatically
 - Voting result calculated according to predefined or present attendance
 - ◆ Rating
- Key-press sign-in
- Automatic detection

Interconnections

- 1.5 m cable with 6P-DIN plug
- 0.6 m cable with 6P-DIN socket

Technical Specifications

Mechanical

Mounting.....Flush-mounting
 Dimensions (h x w x d) (w/o stem microphone)....83 x 111 x 41 mm
 Weight.....93 g
 Color.....Silver/Charcoal gray

Ordering Information

HCS-3643NDTE.....Economical Voting System Delegate Unit
 (flush-mounting, 3 voting keys, silver)
 HCS-3643NDTE_G.....Economical Voting System Delegate Unit
 (flush-mounting, 3 voting keys, charcoal gray)

HCS-3643NCTKE Voting Unit with IC-Card Reader



Ordering Information

- HCS-3643NCTKE.....Economical Voting System Chairman Unit
(flush-mounting, 3 voting keys, IC-Card, silver)
- HCS-3643NCTKE_G...Economical Voting System Chairman Unit
(flush-mounting, 3 voting keys, IC-Card, charcoal gray)

Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 3 voting keys
- Controls voting start and stop
- Built-in IC-card reader

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - Pass-rate setup, voting result calculated automatically
 - Voting result calculated according to predefined or present attendance
 - ◆ Rating
- Controls voting start and stop
- Built-in IC-card reader
- Key-press sign-in
- Automatic detection

Interconnections

- 1.5 m cable with 6P-DIN plug
- 0.6 m cable with 6P-DIN socket

Technical Specifications

Mechanical

Mounting.....Flush-mounting
 Dimensions (h x w x d) (w/o stem microphone).....83 x 111 x 41 mm
 Weight.....93 g
 Color.....Silver/Charcoal gray

HCS-3643NDTKE Voting Unit with IC-Card Reader



Ordering Information

- HCS-3643NDTKE.....Economical Voting System Delegate Unit
(flush-mounting, 3 voting keys, IC-Card, silver)
- HCS-3643NDTKE_G.....Economical Voting System Delegate Unit
(flush-mounting, 3 voting keys, IC-Card, charcoal gray)

Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 3 voting keys
- Built-in IC-card reader

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - Pass-rate setup, voting result calculated automatically
 - Voting result calculated according to predefined or present attendance
 - ◆ Rating
- Built-in IC-card reader
- Key-press sign-in
- Automatic detection

Interconnections

- 1.5 m cable with 6P-DIN plug
- 0.6 m cable with 6P-DIN socket

Technical Specifications

Mechanical

Mounting.....Flush-mounting
 Dimensions (h x w x d) (w/o stem microphone)....83 x 111 x 41 mm
 Weight.....93 g
 Color.....Silver/Charcoal gray