

## HCS-4326CKE/50 Voting Unit with Channel Selection and IC-card Reader



HCS-4325CKE\_G/50+HCS-4327HD/50



HCS-4325CKE\_S/50+HCS-4327C/50

### Features

- Flush-mounting, stylish and ergonomic design
- 5 voting keys
- Controls voting start and stop
- "Closed Loop - Daisy Chain" connection topology
- 64 language channels for simultaneous interpretation, all channels with a frequency response of 30 Hz to 20 kHz
- Built-in channel selector consists of up/down channel select buttons and 2-digit channel indicator display
- Excellent immunity to RF interference from mobile phones
- Supporting "PnP" (plug and play)
- Automatically adapts to available channels
- No audio output until the headphone is connected
- Built-in contactless IC-card reader

- Mostly cooperated with handheld microphone HCS-4327HD/50 for flush-mounting into armrests of seats, or cooperated with HCS-4327C/D/50 for flush-mounting into desktop

The Chairman Unit with voting and channel selector enables participants to listen to the speaker and vote. The unit has five voting buttons for all types of voting. The indicators of the voting buttons are used to prompt users to register their presence and to confirm their vote. The unit has a built-in channel selector, which makes simultaneous interpretations available. The channel selector includes up and down channel select buttons and a 2-digit channel indicator display, enabling rapid selection of the required language channel. Channel selection is automatically limited to the number of language channels available.

Similar in appearance to HCS-4326DKE/50 Delegate Unit, the HCS-4326CKE/50 Chairman Unit can be used to start or stop voting.

### Functions

- Compliant to IEC 60914
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a congress unit and connection failure of a cable will not influence other congress units in the system
- 64 language channels for simultaneous interpretation, all channels with a frequency response of 30 Hz to 20 kHz
- Automatic recovery facility, supporting "PnP" (plug and play)
- Excellent immunity to RF interference from mobile phones and comparable devices
- 5 voting keys
- Every delegate unit is assigned an individual ID for convenient setup and to avoid double ID forever
- Multifunction voting in combination with the corresponding software modules:
  - ◆ For/Against
  - ◆ Parliamentary: YES/NO/ABSTAIN
  - ◆ Questionnaire: 1/2/3/4/5
  - ◆ Audience response: --/-/0/+/>++
  - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
  - ◆ Appraisal:
    - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied) (Three keys voting: satisfied/basically satisfied/unsatisfied) (Two keys voting: satisfied/unsatisfied)
    - Qualified (four/three/two keys voting)
    - Competent (four/three/two keys voting)
- Built-in contactless IC-card reader
- Key-press sign-in
- Automatic video tracking implementation when cooperating with cameras, video switcher unit; preset positions on PC
- Controls voting start and stop

**Controls and Indicators**

- Built-in channel selector consists with up/down channel select buttons and 2-digit channel indicator display
- Headphone volume up and down
- Five voting keys with indicators

**Interconnections**

- 6P mini DIN socket for external microphone
- Ø 3.5 mm stereo headphone jack
- 1.5 m cable with 6P-DIN plug
- 0.6 m cable with 6P-DIN socket

**Technical Specifications**

**Electrical**

Max. consumption ..... 1.3 W

**Headphone connection**

Frequency response ..... 30 Hz to 20 kHz

Earphone load impedance ..... >16 Ohm

Earphone output ..... 10 mW

**Interface data**

Connector ..... Ø 3.5 mm stereo jacks for headphone  
 ..... 6P mini DIN socket for handheld microphone

**Mechanical**

Mounting ..... Flush-mounting

Dimensions (h x w x d) ..... 86 x 139 x 40 mm

Weight ..... 0.4 kg

Color ..... Charcoal gray / Silver

**Ordering Information**

HCS-4326CKE\_S/50 ..... Fully Digital Congress System Chairman  
 Unit (flush-mounting, 5 voting keys,  
 IC-Card, 64 CHs, silver)

HCS-4326CKE\_G/50 ..... Fully Digital Congress System Chairman  
 Unit (flush-mounting, 5 voting keys,  
 IC-Card, 64 CHs, charcoal gray)

## HCS-4326DKE/50 Voting Unit with Channel Selection and IC-card Reader



HCS-4325DKE\_G/50+HCS-4327HD/50



HCS-4325DKE\_S/50+HCS-4327D/50

### Features

- Flush-mounting, stylish and ergonomic design
- 5 voting keys
- "Closed Loop - Daisy Chain" connection topology
- 64 language channels for simultaneous interpretation, all channels with a frequency response of 30 Hz to 20 kHz
- Built-in channel selector consists of up/down channel select buttons and 2-digit channel indicator display
- Excellent immunity to RF interference from mobile phones
- Supporting "PnP" (plug and play)
- Automatically adapts to available channels
- No audio output until the headphone is connected
- Built-in contactless IC-card reader
- Mostly cooperated with handheld microphone HCS-4327HD/50 for flush-mounting into armrests of seats, or cooperated with HCS-4327C/D/50 for flush-mounting into desktop

The Chairman Unit with voting and channel selector enables participants to listen to the speaker and vote. The unit has five voting buttons for all types of voting. The indicators of the voting buttons are used to prompt users to register their presence and to confirm their vote. The unit has a built-in channel selector, which makes simultaneous interpretations available. The channel selector includes up and down channel select buttons and a 2-digit channel indicator display, enabling rapid selection of the required language channel. Channel selection is automatically limited to the number of language channels available.

### Functions

- Compliant to IEC 60914
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a congress unit and connection failure of a cable will not influence other congress units in the system
- 64 language channels for simultaneous interpretation, all channels with a frequency response of 30 Hz to 20 kHz
- Automatic recovery facility, supporting "PnP" (plug and play)
- Excellent immunity to RF interference from mobile phones and comparable devices
- 5 voting keys
- Every delegate unit is assigned an individual ID for convenient setup and to avoid double ID forever
- Multifunction voting in combination with the corresponding software modules:
  - ◆ For/Against
  - ◆ Parliamentary: YES/NO/ABSTAIN
  - ◆ Questionnaire: 1/2/3/4/5
  - ◆ Audience response: --/0/+/++
  - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
  - ◆ Appraisal:
    - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied) (Three keys voting: satisfied/basically satisfied/unsatisfied) (Two keys voting: satisfied/unsatisfied)
    - Qualified (four/three/two keys voting)
    - Competent (four/three/two keys voting)
- Built-in contactless IC-card reader
- Key-press sign-in
- Automatic video tracking implementation when cooperating with cameras, video switcher unit; preset positions on PC

### Controls and Indicators

- Built-in channel selector consists with up/down channel select buttons and 2-digit channel indicator display
- Headphone volume up and down
- Five voting keys with indicators

### Interconnections

- 6P mini DIN socket for external microphone
- Ø 3.5 mm stereo headphone jack
- 1.5 m cable with 6P-DIN plug
- 0.6 m cable with 6P-DIN socket

**Technical Specifications**

**Electrical**

Max. consumption..... 1.3 W

**Headphone connection**

Frequency response..... 30 Hz to 20 kHz

Earphone load impedance..... >16 Ohm

Earphone output..... 10 mW

**Interface data**

Connector..... Ø 3.5 mm stereo jacks for headphone  
 ..... 6P mini DIN socket for handheld microphone

**Mechanical**

Mounting..... Flush-mounting

Dimensions (h x w x d)..... 86 x 139 x 40 mm

Weight..... 0.4 kg

Color..... Charcoal gray / Silver

**Ordering Information**

HCS-4326DKE\_S/50..... Fully Digital Congress System Delegate  
 Unit (flush-mounting, 5 voting keys,  
 IC-Card, 64 CHs, silver)

HCS-4326DKE\_G/50..... Fully Digital Congress System Delegate  
 Unit (flush-mounting, 5 voting keys,  
 IC-Card, 64 CHs, charcoal gray)

## HCS-4326DE/50 Voting Unit with Channel Selection



HCS-4325DE\_G/50+HCS-4327HD/50



HCS-4325DE\_S/50+HCS-4327D/50

### Features

- Flush-mounting, stylish and ergonomic design
- 5 voting keys
- "Closed Loop - Daisy Chain" connection topology
- 64 language channels for simultaneous interpretation, all channels with a frequency response of 30 Hz to 20 kHz
- Built-in channel selector consists of up/down channel select buttons and 2-digit channel indicator display
- Excellent immunity to RF interference from mobile phones
- Supporting "PnP" (plug and play)
- Automatically adapts to available channels
- No audio output until the headphone is connected
- Mostly cooperated with handheld microphone HCS-4327HD/50 for flush-mounting into armrests of seats, or cooperated with HCS-4327C/D/50 for flush-mounting into desktop

The Chairman Unit with voting and channel selector enables participants to listen to the speaker and vote. The unit has five voting buttons for all types of voting. The indicators of the voting buttons are used to prompt users to register their presence and to confirm their vote. The unit has a built-in channel selector, which makes simultaneous interpretations available. The channel selector includes up and down channel select buttons and a 2-digit channel indicator display, enabling rapid selection of the required language channel. Channel selection is automatically limited to the number of language channels available.

### Functions

- Compliant to IEC 60914
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a congress unit and connection failure of a cable will not influence other congress units in the system
- 64 language channels for simultaneous interpretation, all channels with a frequency response of 30 Hz to 20 kHz
- Automatic recovery facility, supporting "PnP" (plug and play)
- Excellent immunity to RF interference from mobile phones and comparable devices
- 5 voting keys
- Every delegate unit is assigned an individual ID for convenient setup and to avoid double ID forever
- Multifunction voting in combination with the corresponding software modules:
  - ◆ For/Against
  - ◆ Parliamentary: YES/NO/ABSTAIN
  - ◆ Questionnaire: 1/2/3/4/5
  - ◆ Audience response: --/-/0/+/>+++
  - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
  - ◆ Appraisal:
    - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied) (Three keys voting: satisfied/basically satisfied/unsatisfied) (Two keys voting: satisfied/unsatisfied)
    - Qualified (four/three/two keys voting)
    - Competent (four/three/two keys voting)
- Key-press sign-in
- Automatic video tracking implementation when cooperating with cameras, video switcher unit; preset positions on PC

### Controls and Indicators

- Built-in channel selector consists with up/down channel select buttons and 2-digit channel indicator display
- Headphone volume up and down
- Five voting keys with indicators

### Interconnections

- 6P mini DIN socket for external microphone
- Ø 3.5 mm stereo headphone jack
- 1.5 m cable with 6P-DIN plug
- 0.6 m cable with 6P-DIN socket

**Technical Specifications**

**Electrical**

Max. consumption..... 1.3 W

**Headphone connection**

Frequency response.....30 Hz to 20 kHz

Earphone load impedance.....>16 Ohm

Earphone output..... 10 mW

**Interface data**

Connector.....Ø 3.5 mm stereo jacks for headphone  
 .....6P mini DIN socket for handheld microphone

**Mechanical**

Mounting..... Flush-mounting

Dimensions (h x w x d)..... 86 x 139 x 40 mm

Weight..... 0.4 kg

Color.....Charcoal gray / Silver

**Ordering Information**

HCS-4326DE\_S/50.....Fully Digital Congress System Delegate  
 Unit (flush-mounting, 5 voting keys, 64  
 CHs, silver)

HCS-4326DE\_G/50.....Fully Digital Congress System Delegate  
 Unit (flush-mounting, 5 voting keys, 64  
 CHs, charcoal gray)