

## HCS-4340CA/50 Multi-function Connector



### Functions

- Direct or indirect connection with discussion unit, voting unit and channel selector
- “Closed Loop - Daisy Chain” connection topology
- Data transmission between the units by patented “MCA-STREAM” technology
- Automatic recovery facility, supporting “PnP”(plug and play)

### Interconnections

- Built-in 4 x RJ45 interface:
  - ◆ HCS-4340CA/50 can connect 1 voting unit, 1 chairman unit and 1 channel selector
- Ø 3.5 mm socket for loudspeaker
- 2 m cable with 6P-DIN plug for connection to system CMU or to another Multi-function Connector
- 6P-DIN standard socket for loop-through interconnection

### Technical Specifications

#### Electrical

Max. consumption.....2.1 W

#### Mechanical

Mounting.....Fixed mounting  
 Dimensions (h x w x d).....35 x 170 x 112 mm  
 Weight.....0.85 kg  
 Color.....Gray

### Ordering Information

HCS-4340CA/50.....Multi-function Connector (for connection to 1 chairman unit + 1 voting unit + 1 channel selector, gray)

## HCS-4340DA/50 Multi-function Connector



### Functions

- Direct or indirect connection with discussion unit, voting unit and channel selector
- “Closed Loop - Daisy Chain” connection topology
- Data transmission between the units by patented “MCA-STREAM” technology
- Automatic recovery facility, supporting “PnP”(plug and play)

### Interconnections

- Built-in 4 x RJ45 interface:
  - ◆ HCS-4340DA/50 can connect 1 voting unit, 1 delegate unit and 1 channel selector
- Ø 3.5 mm socket for loudspeaker
- 2 m cable with 6P-DIN plug for connection to system CMU or to another Multi-function Connector
- 6P-DIN standard socket for loop-through interconnection

### Technical Specifications

#### Electrical

Max. consumption.....2.1 W

#### Mechanical

Mounting.....Fixed mounting  
 Dimensions (h x w x d).....35 x 170 x 112 mm  
 Weight.....0.85 kg  
 Color.....Gray

### Ordering Information

HCS-4340DA/50.....Multi-function Connector (for connection to 1 delegate unit + 1 voting unit + 1 channel selector, gray)

## HCS-4340HDA/50 Multi-function Connector



### Functions

- Direct or indirect connection with discussion unit, voting unit and channel selector
- “Closed Loop - Daisy Chain” connection topology
- Data transmission between the units by patented “MCA-STREAM” technology
- Automatic recovery facility, supporting “PnP”(plug and play)

### Interconnections

- Built-in 4 x RJ45 interface:
  - ◆ HCS-4340HDA/50 can connect 1 voting unit and 1 channel selector
- Ø 3.5 mm socket for loudspeaker
- 6P mini DIN socket for handheld microphone
- 2 m cable with 6P-DIN plug for connection to system CMU or to another Multi-function Connector
- 6P-DIN standard socket for loop-through interconnection

### Technical Specifications

#### Electrical

Max. consumption.....2.1 W

#### Mechanical

Mounting.....Fixed mounting  
 Dimensions (h x w x d).....35 x 170 x 112 mm  
 Weight.....0.85 kg  
 Color.....Gray

### Ordering Information

HCS-4340HDA/50.....Multi-function Connector (for connection to 1 handheld delegate unit + 1 voting unit + 1 channel selector, gray)

## HCS-4340B/50 Multi-function Connector



### Functions

- Direct or indirect connection with channel selector
- “Closed Loop - Daisy Chain” connection topology
- Data transmission between the units by patented “MCA-STREAM” technology
- Automatic recovery facility, supporting “PnP” (plug and play)

### Interconnections

- Built-in 4 x RJ45 interface:
  - ◆ HCS-4340B/50 can connect 4 pcs channel selectors
- 2 m cable with 6P-DIN plug for connection to system CMU or to another Multi-function Connector
- 6P-DIN standard socket for loop-through interconnection

### Technical Specifications

#### Electrical

Max. consumption.....2.1 W

#### Mechanical

Mounting.....Fixed mounting  
 Dimensions (h x w x d).....35 x 170 x 112 mm  
 Weight.....0.85 kg  
 Color.....Gray

### Ordering Information

HCS-4340B/50.....Multi-function Connector (for connection to 4 pcs of channel selectors, gray)

## HCS-4340DT/50 Multi-function Connector




---

### Functions

- Direct or indirect connection with discussion unit or channel selector
- “Closed Loop - Daisy Chain” connection topology
- Data transmission between the units by patented “MCA-STREAM” technology
- Automatic recovery facility, supporting “PnP”(plug and play)

### Interconnections

- Built-in 4 x RJ45 interface:
  - ◆ HCS-4340DT/50 can connect 2 delegate units and 2 channel selectors
- Ø 3.5 mm socket for loudspeaker
- 2 m cable with 6P-DIN plug for connection to system CMU or to another Multi-function Connector
- 6P-DIN standard socket for loop-through interconnection

---

### Technical Specifications

#### Electrical

Max. consumption.....2.1 W

#### Mechanical

Mounting.....Fixed mounting

Dimensions (h x w x d).....35 x 170 x 112 mm

Weight.....0.85 kg

Color.....Gray

---

### Ordering Information

HCS-4340DT/50.....Multi-function Connector (for connection to 2 delegate units + 2 channel selectors, gray)

System Connection

