

HCS-4368CF/50 Voting Unit



Features

- **Tabletop-mounting, stylish and ergonomic design**
- **Max system capacity: 4096 voting units**
- **5 voting keys**
- **“Closed Loop - Daisy Chain” connection topology**
- **Controls voting start, suspend, re-start and stop**
- **Waterproof facility**

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 12 kV static, excels IEC CISPR 24
- Max system capacity: 4096 voting units
- 5 voting keys
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a congress unit and connection failure of a cable will not influence other congress units in the system
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - ◆ Questionnaire: 1/2/3/4/5
 - ◆ Audience response: --/0/+/++
 - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
 - ◆ Appraisal:
 - Satisfied (Four keys voting: perfectly satisfied/satisfied/basicly satisfied/unsatisfied)
(Three keys voting: satisfied/basicly satisfied/unsatisfied)
(Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Controls voting start, suspend, re-start and stop
- Graphic 256x32 LCD with back-lighting for displaying:
 - ◆ Delegate signed-in and voting results, etc.
 - ◆ Messages (messages from system administrator to all or part of participants)
 - ◆ Multilingual (simplified/traditional Chinese and English, etc.) menu
- Key-press sign-in
- Automatic detection
- Waterproof facility

Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

Technical Specifications

Electrical

Max. consumption.....1.8 W

Mechanical

Mounting.....Tabletop mounting

Dimensions (h x w x d).....64 x 197 x 86 mm

Weight.....0.49 kg

Color.....Red

Ordering Information

HCS-4368CF_R/50.....Fully Digital Voting System Chairman Unit
(tabletop, 5 voting keys, 256x32 LCD,
waterproof, antistatic 12000 V, red)

HCS-4368DF/50 Voting Unit



Features

- **Tabletop-mounting, stylish and ergonomic design**
- **Max system capacity: 4096 voting units**
- **5 voting keys**
- **“Closed Loop - Daisy Chain” connection topology**
- **Waterproof facility**

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 12 kV static, excels IEC CISPR 24
- Max system capacity: 4096 voting units
- 5 voting keys
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a congress unit and connection failure of a cable will not influence other congress units in the system
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - ◆ Questionnaire: 1/2/3/4/5
 - ◆ Audience response: --/0/+/++
 - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
 - ◆ Appraisal:
 - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied)
(Three keys voting: satisfied/basically satisfied/unsatisfied)
(Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Graphic 256x32 LCD with back-lighting for displaying:
 - ◆ Delegate signed-in and voting results, etc.
 - ◆ Messages (messages from system administrator to all or part of participants)
 - ◆ Multilingual (simplified/traditional Chinese and English, etc.) menu
- Key-press sign-in
- Automatic detection
- Waterproof facility

Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

Technical Specifications

Electrical

Max. consumption.....1.8 W

Mechanical

Mounting.....Tabletop mounting
 Dimensions (h x w x d).....64 x 197 x 86 mm
 Weight.....0.49 kg
 Color.....Red

Ordering Information

HCS-4368DF_R/50.....Fully Digital Voting System Delegate Unit
 (tabletop, 5 voting keys, 256x32 LCD, waterproof, antistatic 12000 V, red)

HCS-4368CFK/50 Voting Unit with IC-Card Reader



Features

- **Tabletop-mounting, stylish and ergonomic design**
- **Max system capacity: 4096 voting units**
- **5 voting keys**
- **“Closed Loop - Daisy Chain” connection topology**
- **Controls voting start, suspend, re-start and stop**
- **Built-in IC-card reader**

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 5 voting keys
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a congress unit and connection failure of a cable will not influence other congress units in the system
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - ◆ Questionnaire: 1/2/3/4/5
 - ◆ Audience response: --/0/+/++
 - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
 - ◆ Appraisal:
 - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied)
(Three keys voting: satisfied/basically satisfied/unsatisfied)
(Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Controls voting start, suspend, re-start and stop
- Graphic 256x32 LCD with back-lighting for displaying:
 - ◆ Delegate signed-in and voting results, etc.
 - ◆ Messages (messages from system administrator to all or part of participants)
 - ◆ Multilingual (simplified/traditional Chinese and English, etc.) menu
- Built-in IC-card reader
- Key-press sign-in
- Automatic detection

Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

Technical Specifications

Electrical

Max. consumption.....1.8 W

Mechanical

Mounting.....Tabletop mounting
 Dimensions (h x w x d).....64 x 197 x 86 mm
 Weight.....0.49 kg
 Color.....Red

Ordering Information

HCS-4368CFK_R/50.....Fully Digital Voting System Chairman Unit (tabletop, 5 voting keys, 256x32 LCD, IC-Card, red)

HCS-4368DFK/50 Voting Unit with IC-Card Reader



Features

- **Tabletop-mounting, stylish and ergonomic design**
- **Max system capacity: 4096 voting units**
- **5 voting keys**
- **“Closed Loop - Daisy Chain” connection topology**
- **Built-in IC-card reader**

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 5 voting keys
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a congress unit and connection failure of a cable will not influence other congress units in the system
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - ◆ Questionnaire: 1/2/3/4/5
 - ◆ Audience response: --/0/+/++
 - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
 - ◆ Appraisal:
 - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied)
(Three keys voting: satisfied/basically satisfied/unsatisfied)
(Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Graphic 256x32 LCD with back-lighting for displaying:
 - ◆ Delegate signed-in and voting results, etc.
 - ◆ Messages (messages from system administrator to all or part of participants)
 - ◆ Multilingual (simplified/traditional Chinese and English, etc.) menu
- Built-in IC-card reader
- Key-press sign-in
- Automatic detection

Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

Technical Specifications

Electrical

Max. consumption.....1.8 W

Mechanical

Mounting.....Tabletop mounting

Dimensions (h x w x d).....64 x 197 x 86 mm

Weight.....0.49 kg

Color.....Red

Ordering Information

HCS-4368DFK_R/50.....Fully Digital Voting System Delegate Unit (tabletop, 5 voting keys, 256x32 LCD, IC-Card, red)

HCS-4368CF/FM/50 Voting Unit



Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 5 voting keys
- “Closed Loop - Daisy Chain” connection topology
- Controls voting start, suspend, re-start and stop
- Waterproof facility, and equipped with ferromagnetic cover to protect the unit from damage during the adjournment

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 12 kV static, excels IEC CISPR 24
- Max system capacity: 4096 voting units
- 5 voting keys
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a congress unit and connection failure of a cable will not influence other congress units in the system
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - ◆ Questionnaire: 1/2/3/4/5
 - ◆ Audience response: --/-/0/+/>++
 - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
 - ◆ Appraisal:
 - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied)
(Three keys voting: satisfied/basically satisfied/unsatisfied)
(Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Controls voting start, suspend, re-start and stop
- Graphic 256x32 LCD with back-lighting for displaying:
 - ◆ Delegate signed-in and voting results, etc.
 - ◆ Messages (messages from system administrator to all or part of participants)
 - ◆ Multilingual (simplified/traditional Chinese and English, etc.) menu
- Key-press sign-in
- Automatic detection
- Waterproof facility, and equipped with ferromagnetic cover to protect the unit from damage during the adjournment

Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

Technical Specifications

Electrical

Max. consumption.....1.8 W

Mechanical

Mounting.....Flush-mounting
 Dimensions (h x w x d).....60 x 197 x 86 mm
 Weight.....0.61 kg
 Color.....Silver/Red

Ordering Information

- HCS-4368CF/FM_R/50.....Fully Digital Voting System Chairman Unit (flush-mounting, 5 voting keys, 256x32 LCD, waterproof, antistatic 12000 V, cover, red)
- HCS-4368CF/FM_S/50.....Fully Digital Voting System Chairman Unit (flush-mounting, 5 voting keys, 256x32 LCD, waterproof, antistatic 12000 V, cover, silver)

HCS-4368DF/FM/50 Voting Unit



Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 5 voting keys
- “Closed Loop - Daisy Chain” connection topology
- Waterproof facility, and equipped with ferromagnetic cover to protect the unit from damage during the adjournment

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 12 kV static, excels IEC CISPR 24
- Max system capacity: 4096 voting units
- 5 voting keys
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a congress unit and connection failure of a cable will not influence other congress units in the system
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - ◆ Questionnaire: 1/2/3/4/5
 - ◆ Audience response: --/-/0/+/>++
 - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
 - ◆ Appraisal:
 - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied)
(Three keys voting: satisfied/basically satisfied/unsatisfied)
(Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Graphic 256x32 LCD with back-lighting for displaying:
 - ◆ Delegate signed-in and voting results, etc.
 - ◆ Messages (messages from system administrator to all or part of participants)
 - ◆ Multilingual (simplified/traditional Chinese and English, etc.) menu
- Key-press sign-in
- Automatic detection
- Waterproof facility, and equipped with ferromagnetic cover to protect the unit from damage during the adjournment

Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

Technical Specifications

Electrical

Max. consumption.....1.8 W

Mechanical

Mounting.....Flush-mounting
 Dimensions (h x w x d).....60 x 197 x 86 mm
 Weight.....0.61 kg
 Color.....Silver/Red

Ordering Information

HCS-4368DF/FM_R/50.....Fully Digital Voting System Delegate Unit (flush-mounting, 5 voting keys, 256x32 LCD, waterproof, antistatic 12000 V, cover, red)

HCS-4368DF/FM_S/50.....Fully Digital Voting System Delegate Unit (flush-mounting, 5 voting keys, 256x32 LCD, waterproof, antistatic 12000 V, cover, silver)

HCS-4368CFK/FM/50 Voting Unit with IC-Card Reader



Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 5 voting keys
- “Closed Loop - Daisy Chain” connection topology
- Controls voting start, suspend, re-start and stop
- Built-in IC-card reader
- Equipped with ferromagnetic cover to protect the unit from damage during the adjournment

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 5 voting keys
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a congress unit and connection failure of a cable will not influence other congress units in the system
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - ◆ Questionnaire: 1/2/3/4/5
 - ◆ Audience response: --/0/+/++
 - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
 - ◆ Appraisal:
 - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied)
(Three keys voting: satisfied/basically satisfied/unsatisfied)
(Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Controls voting start, suspend, re-start and stop
- Graphic 256x32 LCD with back-lighting for displaying:
 - ◆ Delegate signed-in and voting results, etc.
 - ◆ Messages (messages from system administrator to all or part of participants)
 - ◆ Multilingual (simplified/traditional Chinese and English, etc.) menu
- Built-in IC-card reader

- Key-press sign-in
- Automatic detection
- Equipped with ferromagnetic cover to protect the unit from damage during the adjournment

Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

Technical Specifications

Electrical

Max. consumption.....1.8 W

Mechanical

Mounting.....Flush-mounting
 Dimensions (h x w x d).....60 x 197 x 86 mm
 Weight.....0.61 kg
 Color.....Silver/Red

Ordering Information

- HCS-4368CFK/FM_R/50.....Fully Digital Voting System Chairman Unit (flush-mounting, 5 voting keys, 256x32 LCD, IC-Card, cover, red)
- HCS-4368CFK/FM_S/50.....Fully Digital Voting System Chairman Unit (flush-mounting, 5 voting keys, 256x32 LCD, IC-Card, cover, silver)

HCS-4368DFK/FM/50 Voting Unit with IC-Card Reader



Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 5 voting keys
- "Closed Loop - Daisy Chain" connection topology
- Built-in IC-card reader
- Equipped with ferromagnetic cover to protect the unit from damage during the adjournment

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 5 voting keys
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a congress unit and connection failure of a cable will not influence other congress units in the system
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - ◆ Questionnaire: 1/2/3/4/5
 - ◆ Audience response: --/-/0/+/>++
 - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
 - ◆ Appraisal:
 - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied)
(Three keys voting: satisfied/basically satisfied/unsatisfied)
(Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Graphic 256x32 LCD with back-lighting for displaying:
 - ◆ Delegate signed-in and voting results, etc.
 - ◆ Messages (messages from system administrator to all or part of participants)
 - ◆ Multilingual (simplified/traditional Chinese and English, etc.) menu
- Built-in IC-card reader
- Key-press sign-in
- Automatic detection
- Equipped with ferromagnetic cover to protect the unit from damage during the adjournment

Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

Technical Specifications

Electrical

Max. consumption.....1.8 W

Mechanical

Mounting.....Flush-mounting
 Dimensions (h x w x d).....60 x 197 x 86 mm
 Weight.....0.61 kg
 Color.....Silver/Red

Ordering Information

HCS-4368DFK/FM_R/50.....Fully Digital Voting System Delegate Unit (flush-mounting, 5 voting keys, 256x32 LCD, IC-Card, cover, red)

HCS-4368DFK/FM_S/50.....Fully Digital Voting System Delegate Unit (flush-mounting, 5 voting keys, 256x32 LCD, IC-Card, cover, silver)