

HCS-4843NCFE/50 Voting Unit



Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 5 voting keys
- Controls voting start and stop

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 5 voting keys
- In combination with corresponding software modules, multifunction voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - ◆ Questionnaire: 1/2/3/4/5
 - ◆ Audience response: --/0/+/++
 - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
 - ◆ Appraisal:
 - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied)
(Three keys voting: satisfied/basically satisfied/unsatisfied)
(Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Controls voting start and stop
- Key-press sign-in
- Automatic detection

Interconnections

- RJ45 standard interface
- Used with HCS-4340CA/50 (Multi-function Connector)

Technical Specifications

Mechanical

Mounting.....Flush-mounting
 Dimensions (h x w x d).....83 x 111 x 41 mm
 Weight.....93 g
 Color.....Charcoal gray / Silver

Ordering Information

- HCS-4843NCFE_S/50.....Fully Digital Voting System Chairman Unit (flush-mounting, 5 voting keys, HCS-4340CA/50 needed, silver)
- HCS-4843NCFE_G/50.....Fully Digital Voting System Chairman Unit (flush-mounting, 5 voting keys, HCS-4340CA/50 needed, charcoal gray)

HCS-4843NDFE/50 Voting Unit



Ordering Information

HCS-4843NDFE_S/50 ___ Fully Digital Voting System Delegate Unit (flush-mounting, 5 voting keys, HCS-4340DA/HDA/50 needed, silver)

HCS-4843NDFE_G/50 ___ Fully Digital Voting System Delegate Unit (flush-mounting, 5 voting keys, HCS-4340DA/HDA/50 needed, charcoal gray)

Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 5 voting keys

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 5 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - ◆ Questionnaire: 1/2/3/4/5
 - ◆ Audience response: --/0/+/++
 - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
 - ◆ Appraisal:
 - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied) (Three keys voting: satisfied/basically satisfied/unsatisfied) (Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Key-press sign-in
- Automatic detection

Interconnections

- RJ45 standard interface
- Used with HCS-4340DA/HDA/50 (Multi-function Connector)

Technical Specifications

Mechanical

Mounting.....Flush-mounting
 Dimensions (h x w x d).....83 x 111 x 41 mm
 Weight.....93 g
 Color.....Charcoal gray / Silver

HCS-4843NCFKE/50 Voting Unit with IC-Card Reader



Ordering Information

- HCS-4843NCFKE_S/50.....Fully Digital Voting System Chairman Unit (flush-mounting, 5 voting keys, IC-Card, HCS-4340CA/50 needed, silver)
- HCS-4843NCFKE_G/50.....Fully Digital Voting System Chairman Unit (flush-mounting, 5 voting keys, IC-Card, HCS-4340CA/50 needed, charcoal gray)

Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 5 voting keys
- Controls voting start and stop
- Built-in IC-card reader

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 5 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - ◆ Questionnaire: 1/2/3/4/5
 - ◆ Audience response: --/-/0/+ /++
 - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
 - ◆ Appraisal:
 - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied)
(Three keys voting: satisfied/basically satisfied/unsatisfied)
(Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Controls voting start and stop
- Built-in IC-card reader
- Key-press sign-in
- Automatic detection

Interconnections

- RJ45 standard interface
- Used with HCS-4340CA/50 (Multi-function Connector)

Technical Specifications

Mechanical

Mounting.....Flush-mounting
 Dimensions (h x w x d).....83 x 111 x 41 mm
 Weight.....93 g
 Color.....Charcoal gray / Silver

HCS-4843NDFKE/50 Voting Unit with IC-Card Reader



Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 5 voting keys
- Built-in IC-card reader

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 5 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - ◆ Questionnaire: 1/2/3/4/5
 - ◆ Audience response: --/0/+/++
 - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
 - ◆ Appraisal:
 - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied)
(Three keys voting: satisfied/basically satisfied/unsatisfied)
(Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Built-in IC-card reader
- Key-press sign-in
- Automatic detection

Interconnections

- RJ45 standard interface
- Used with HCS-4340DA/HDA/50 (Multi-function Connector)

Technical Specifications

Mechanical

Mounting.....Flush-mounting
 Dimensions (h x w x d).....83 x 111 x 41 mm
 Weight.....93 g
 Color.....Charcoal gray / Silver

Ordering Information

HCS-4843NDFKE_S/50.....Fully Digital Voting System Delegate Unit (flush-mounting, 5 voting keys, IC-Card, HCS-4340DA/HDA/50 needed, silver)

HCS-4843NDFKE_G/50.....Fully Digital Voting System Delegate Unit (flush-mounting, 5 voting keys, IC-Card, HCS-4340DA/HDA/50 needed, charcoal gray)

HCS-4843DFE/50 Voting Unit



Ordering Information

HCS-4843DFE_S/50 _____ Fully Digital Voting System Delegate Unit
(flush-mounting, 5 voting keys, no Multi-function Connector needed, silver)

Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 5 voting keys

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 5 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - ◆ Questionnaire: 1/2/3/4/5
 - ◆ Audience response: --/0/+/++
 - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
 - ◆ Appraisal:
 - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied)
(Three keys voting: satisfied/basically satisfied/unsatisfied)
(Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Key-press sign-in
- Automatic detection

Interconnections

- 1.5 m cable with 6P-DIN plug
- 0.6 m cable with 6P-DIN socket

Technical Specifications

Electrical

Max. consumption _____ 1.3 W

Mechanical

Mounting _____ Flush-mounting
 Dimensions (h x w x d) _____ 83 x 111 x 41 mm
 Weight _____ 0.5 kg
 Color _____ Silver

HCS-4843DFKE/50 Voting Unit with IC-Card Reader



Ordering Information

HCS-4843DFKE_S/50_... Fully Digital Voting System Delegate Unit (flush-mounting, 5 voting keys, IC-Card, no Multi-function Connector needed, silver)

Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 5 voting keys
- Built-in IC-card reader

Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 5 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - ◆ Questionnaire: 1/2/3/4/5
 - ◆ Audience response: --/-/0/+ /++
 - ◆ Parliamentary (NPPV): YES/NO/ABSTAIN/NPPV
 - ◆ Appraisal:
 - Satisfied (Four keys voting: perfectly satisfied/satisfied/basically satisfied/unsatisfied) (Three keys voting: satisfied/basically satisfied/unsatisfied) (Two keys voting: satisfied/unsatisfied)
 - Qualified (four/three/two keys voting)
 - Competent (four/three/two keys voting)
- Built-in IC-card reader
- Key-press sign-in
- Automatic detection

Interconnections

- 1.5 m cable with 6P-DIN plug
- 0.6 m cable with 6P-DIN socket

Technical Specifications

Electrical

Max. consumption..... 1.3 W

Mechanical

Mounting..... Flush-mounting
 Dimensions (h x w x d)..... 83 x 111 x 41 mm
 Weight..... 0.5 kg
 Color..... Silver