

## HCS-4843NCTE/50 Voting Unit



### Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 3 voting keys
- Controls voting start and stop

### Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
  - ◆ For/Against
  - ◆ Parliamentary: YES/NO/ABSTAIN
  - ◆ Appraisal:
    - Satisfied (Three keys voting: satisfied/basically satisfied/unsatisfied)  
(Two keys voting: satisfied/unsatisfied)
    - Qualified (three/two keys voting)
    - Competent (three/two keys voting)
- Controls voting start and stop
- Key-press sign-in
- Automatic detection

### Interconnections

- RJ45 standard interface
- Used with HCS-4340CA/50 (Multi-function Connector)

### Technical Specifications

#### Mechanical

Mounting.....Flush-mounting  
 Dimensions (h x w x d).....83 x 111 x 41 mm  
 Weight.....93 g  
 Color.....Charcoal gray / Silver

### Ordering Information

HCS-4843NCTE\_S/50...Fully Digital Voting System Chairman Unit  
 (flush-mounting, 3 voting keys,  
 HCS-4340CA/50 needed, silver)

HCS-4843NCTE\_G/50...Fully Digital Voting System Chairman Unit  
 (flush-mounting, 3 voting keys,  
 HCS-4340CA/50 needed, charcoal gray)

## HCS-4843NDTE/50 Voting Unit



### Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 3 voting keys

### Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
  - ◆ For/Against
  - ◆ Parliamentary: YES/NO/ABSTAIN
  - ◆ Appraisal:
    - Satisfied (Three keys voting: satisfied/basically satisfied/unsatisfied)  
(Two keys voting: satisfied/unsatisfied)
    - Qualified (three/two keys voting)
    - Competent (three/two keys voting)
- Key-press sign-in
- Automatic detection

### Interconnections

- RJ45 standard interface
- Used with HCS-4340DA/HDA/50 (Multi-function Connector)

### Technical Specifications

#### Mechanical

Mounting.....Flush-mounting  
 Dimensions (h x w x d).....83 x 111 x 41 mm  
 Weight.....93 g  
 Color.....Charcoal gray / Silver

### Ordering Information

HCS-4843NDTE\_S/50...Fully Digital Voting System Delegate Unit  
 (flush-mounting, 3 voting keys,  
 HCS-4340DA/HDA/50 needed, silver)

HCS-4843NDTE\_G/50...Fully Digital Voting System Delegate Unit  
 (flush-mounting, 3 voting keys,  
 HCS-4340DA/HDA/50 needed, charcoal gray)

## HCS-4843NCTKE/50 Voting Unit with IC-Card Reader



### Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 3 voting keys
- Controls voting start and stop
- Built-in IC-card reader

### Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
  - ◆ For/Against
  - ◆ Parliamentary: YES/NO/ABSTAIN
  - ◆ Appraisal:
    - Satisfied (Three keys voting: satisfied/basicly satisfied/unsatisfied)  
(Two keys voting: satisfied/unsatisfied)
    - Qualified (three/two keys voting)
    - Competent (three/two keys voting)
- Controls voting start and stop
- Built-in IC-card reader
- Key-press sign-in
- Automatic detection

### Interconnections

- RJ45 standard interface
- Used with HCS-4340CA/50 (Multi-function Connector)

### Technical Specifications

#### Mechanical

Mounting.....Flush-mounting  
 Dimensions (h x w x d).....83 x 111 x 41 mm  
 Weight.....93 g  
 Color.....Charcoal gray / Silver

### Ordering Information

- HCS-4843NCTKE\_S/50.....Fully Digital Voting System Chairman Unit (flush-mounting, 3 voting keys, IC-Card, HCS-4340CA/50 needed, silver)
- HCS-4843NCTKE\_G/50.....Fully Digital Voting System Chairman Unit (flush-mounting, 3 voting keys, IC-Card, HCS-4340CA/50 needed, charcoal gray)

## HCS-4843NDTKE/50 Voting Unit with IC-Card Reader




---

### Ordering Information

HCS-4843NDTKE\_S/50.....Fully Digital Voting System Delegate Unit (flush-mounting, 3 voting keys, IC-Card, HCS-4340DA/HDA/50 needed, silver)

HCS-4843NDTKE\_G/50.....Fully Digital Voting System Delegate Unit (flush-mounting, 3 voting keys, IC-Card, HCS-4340DA/HDA/50 needed, charcoal gray)

---

### Features

- Flush-mounting, stylish and ergonomic design
- Max system capacity: 4096 voting units
- 3 voting keys
- Built-in IC-card reader

---

### Functions

- New digital design, compliant to many international standards
- Voting system is resistive to 8 kV static, conforms to IEC CISPR 24
- Max system capacity: 4096 voting units
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
  - ◆ For/Against
  - ◆ Parliamentary: YES/NO/ABSTAIN
  - ◆ Appraisal:
    - Satisfied (Three keys voting: satisfied/basically satisfied/unsatisfied) (Two keys voting: satisfied/unsatisfied)
    - Qualified (three/two keys voting)
    - Competent (three/two keys voting)
- Built-in IC-card reader
- Key-press sign-in
- Automatic detection

### Interconnections

- RJ45 standard interface
- Used with HCS-4340DA/HDA/50 (Multi-function Connector)

---

### Technical Specifications

#### Mechanical

Mounting.....Flush-mounting  
 Dimensions (h x w x d).....83 x 111 x 41 mm  
 Weight.....93 g  
 Color.....Charcoal gray / Silver