

**HCS-5100CHG/60
IR Receiver Charging Case**



Features

- Used for charging IR receivers (HCS-5100R)
- Charges 60 pcs of IR receivers per charging
- Uses universal power supply with automatic voltage matching

Controls and Indicators

- Power switch
- Charging indicator on the receiver

Interconnections

- Power output interface
- Power input interface
- Charging lattices

Technical Specifications

Electrical

Mains voltage.....AC 110 V ~ 120 V/220 V ~ 240 V
 Power consumption..... 125 W (60 receivers charging)
 Power consumption (standby)..... 7 W (no receiver in charging case)

Mechanical

Dimensions h x w x d (mm).....260 × 610 × 405
 Net weight..... 14.5 kg (w/o IR receiver)
 Color.....Blue

Ordering Information

HCS-5100CHG/60.....IR Receiver Charging Case (60 pcs/case)

**HCS-5100KS
IR Receiver Storage Case**



Features

- Used for storing and transporting IR receivers
- Every case can store up to 100 IR receivers

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....205 × 669 × 307
 Net weight..... 6 kg (w/o IR receiver)
 Gross weight..... 14 kg (w/100 pcs IR receivers, w/o battery)
 Color.....Blue

Ordering Information

HCS-5100KS.....IR Receiver Storage Case (100 pcs/case)

HCS-5100PA Headphone



Features

- Used with the receiver or a conference unit
- Hi-Fi sound quality
- 32 Ω × 2, Ø 3.5 mm stereo plug
- Frequency response: 20 Hz to 20 kHz
- Sensitivity: ≥108 dBA/1 mW

Ordering Information

HCS-5100PA Headphone

EP-820AS Single Earphone



Features

- Used with the receiver or a conference unit
- Hi-Fi sound quality
- Ø 3.5 mm stereo plug
- 32 Ω (Tip and Sleeve, Ring: NC)
- Frequency response: 50 Hz to 20 kHz
- Sensitivity: ≥102 dBA/1 mW

Ordering Information

EP-820AS Single Earphone (TRS connector, Ring: NC)

HCS-5100PB Headphone



Features

- Used with the receiver or a conference unit
- Hi-Fi sound quality
- 32 Ω × 2, Ø 3.5 mm stereo plug
- Frequency response: 20 Hz to 20 kHz
- Sensitivity: ≥108 dBA/1 mW

Ordering Information

HCS-5100PB Headphone

EP-820BS Single Earphone



Features

- Used with the receiver or a conference unit
- Hi-Fi sound quality
- Ø 3.5 mm stereo plug (TRS)
- 32 Ω (Tip and Sleeve, Ring: NC)
- Frequency response: 20 Hz to 20 kHz
- Sensitivity: ≥108 dBA/1 mW

Ordering Information

EP-820BS Single Earphone (TRS connector, Ring: NC)

EP-828 Single Earphone



Features

- Used with the receiver or a conference unit
- Hi-Fi sound quality
- Built-in mechanical switcher
- Ø 3.5 mm stereo plug (TRS)
- 32 Ω (Tip and Sleeve, Ring: NC)
- Frequency response: 20 Hz to 20 kHz
- Sensitivity: ≥108 dBA/1 mW

Ordering Information

EP-828.....Single Earphone (TRS connector, Ring: NC)

EP-950B Interpreter Headset



Features

- Supplied with the interpreter unit for monitoring and speaking
- Hi-Fi sound quality
- 32 Ω × 2, Ø 3.5 mm stereo plug for headphone
- Ø 3.5 mm stereo plug for microphone (Tip and Sleeve, Ring: NC)
- Frequency response of headphone: 20 Hz to 20 kHz
- Sensitivity of headphone: ≥108 dBA/1 mW
- Frequency response of microphone: 30 Hz to 20 kHz
- Sensitivity of microphone: -46 dBV/Pa

Ordering Information

EP-950B.....Interpreter Headset (stereo)

EP-920BS Earbuds




Features

- Used with the receiver or a conference unit
- Hi-Fi sound quality
- 16 Ω × 2, Ø 3.5 mm stereo plug
- Frequency response: 50 Hz to 20 kHz
- Sensitivity: ≥108 dBA/1 mW

Ordering Information

EP-920BS.....Earbuds (stereo)

Sponge Ear Pads



Features

- Used for HCS-5100PA/HCS-5100PB headphone
- 100 pairs per package
- Color: black

Ordering Information

Sponge Ear Pads.....Sponge Ear Pads

HCS-5100BAT-16 Ni-MH Rechargeable Battery Pack



Features

- Ni-MH rechargeable battery pack
- Suitable for HCS-5100R series digital infrared receiver

Technical Specifications

Electrical

Voltage.....2.4 V
Capacity.....1600 mAh

Mechanical

Dimensions h x w x d (mm).....51 × 27 × 15
Weight.....50 g
Color.....Green

Ordering Information

HCS-5100BAT-16.....Ni-MH Rechargeable Battery Pack

BNC Connector



Features

- Used to connect HCS-5100M/S and HCS-5100T/S or between HCS-5100T/S
- Used with RG-59 Coaxial-cable

Ordering Information

BNC Connector.....BNC Connector (plug)

RG-59 Coaxial-cable



Features

- Equivalent impedance: 75 Ohm
- Ø 5 mm
- Length of per roll: 200-meter

Ordering Information

RG-59.....Coaxial-cable (75 Ω)

HCS-851A/02 Interpreter Booth

Ordering Information

HCS-851A/02.....Interpreter Booth (accommodates 2 interpreters)



HCS-851A/02



HCS-851K

Features

- Compliant to ISO 4043
- Odorless, antistatic, fire-retardant material
- Optimum insulation and sound absorption
- Hinged door (with observation window 0.20 m × 0.22 m), opens outwards, operates silently
- Two front windows and two side windows (dimensions: 0.76 m × 0.85 m each); lower edge of the window: 0.80 m from booth floor
- Booth to hall (and vice versa) - sound pressure level difference: >18 dB (1 kHz)
- Reverberation time inside the booth: between 0.3 s and 0.5 s (octave bands from 125 Hz to 4000 Hz, booth unoccupied)
- Sound pressure level inside the booth by ventilating system ≤40 dBA
- Internal dimensions of the booth h × w × d (cm): 200 × 167 × 160, accommodates two interpreters
- Shipping needs HCS-851K Interpreter Booth Shipping Case
 - ◆ Dimensions of HCS-851K h × w × d (cm): 98×206×74
 - ◆ Weight (incl. the booth): 300 kg

HCS-851A/03 Interpreter Booth



HCS-851A/03



HCS-851K



HCS-851KT

Features

- Compliant to ISO 4043
- Odorless, antistatic, fire-retardant material
- Optimum insulation and sound absorption
- Hinged door (with observation window 0.20 m × 0.22 m), opens outwards, operates silently
- Three front windows and two side windows (dimensions: 0.76 m × 0.85 m each); lower edge of the window: 0.80 m from booth floor
- Booth to hall (and vice versa) - sound pressure level difference: >18 dB (1 kHz)
- Reverberation time inside the booth: between 0.3 s and 0.5 s (octave bands from 125 Hz to 4000 Hz, booth unoccupied)
- Sound pressure level inside the booth by ventilating system ≤40 dBA
- Internal dimensions h × w × d (cm): 200×250×160, accommodates three interpreters
- Shipping needs HCS-851K and HCS-851KT Interpreter Booth Shipping Case
 - ◆ Dimensions of HCS-851K h × w × d (cm): 98×206×74
 - ◆ Dimensions of HCS-851KT h × w × d (cm): 37×210×97
 - ◆ Weight (incl. the booth): 400 kg

Ordering Information

HCS-851A/03.....Interpreter Booth (accommodates 3 interpreters)