


## OC-1N

Optical Video Isolator





The OC-1N is a high performance optical isolator for video or sync signals. It provides complete isolation between devices thus eliminating video hum, ground loops, and DC offsets which can degrade picture quality.





## OC-1N

## **FEATURES**

- Bandwidth 20MHz (- 3dB).
- Channels 1.
- Opto-Isolator Circuitry Extremely linearresponse and wide frequency range compared totraditional transformer based units.
- Level (Gain) and EQ (Peaking) Controls.
- Floating Ground Selection Input.
- Desktop Size Compact size. Two units can berack mounted side-by-side in a 1U rack spacewith the optional RK-50RN adapter.

## **TECHNICAL SPECIFICATIONS**

INPUT: 1 Composite Video,  $1Vpp/75 \Omega$ 

on a BNC.

OUTPUT: 1 Composite Video,  $1Vpp/75\Omega$ 

on a BNC.

S/N RATIO: 69 dB.

BANDWIDTH: 20 MHz -3dB.

DIMENSIONS: 16.5cm x 12cm x4.5cm (6.5"

x4.7" x 1.8", W, D, H.).

POWER 230 VAC, 50/60 Hz, (115VAC,

SOURCE: U.S.A.) 2.3 VA.

WEIGHT: 0.72 kg. (1.6 lbs.) Approx.

ACCESSORIES: Power cord.

OPTIONS: RK-50RN, 19" rack adapter