


## PT-102S

1:2 s-Video Distribution Amplifier





The Kramer PT102S is a high performance video distribution amplifier for s-Video (Y/C) video signals. It takes one input, provides correct buffering and isolation, and distributes the signal to two identical outputs.





## PT-102S

## **FEATURES**

- Bandwidth (Y) 150MHz (- 3dB).
- Y & C Level (Gain) Controls.
- Ultra-compact Part of the Kramer PicoTOOLSTM family ofextremely compact, high quality and cost effective solutions.

## **TECHNICAL SPECIFICATIONS**

INPUT: 1 s-Video, 1Vpp /  $75\Omega$  (Y),

0.3Vpp / 75Ω (C) on a4P

connector.

OUTPUTS: 2 s-Video,  $1Vpp / \Omega(Y)$ ,

0.3Vpp / Ω (C) on4P

connectors.

VIDEO 15

150 MHz. -3dB (Y)

BANDWIDTH:

COUPLING: AC.

DIFF. GAIN: 0.03%

DIFF. PHASE: 0.03 Deg.

CONTROLS: Gain: 8 dB, each "Y" and "C" via

trimmers accessible from front

panel.

S/N RATIO: 78 dB. K-FACTOR: <0.05%

MAX. VIDEO 2 Vpp.

OUTPUT:

POWER SOURCE: 12 VDC, 30 mA.

DIMENSIONS: 6cm x 6.5cm x 2.5cm (2.36" x

2.56" x 1", W, D, H.)

WEIGHT: 0.12 kg. (0.26 lbs.) Approx.

ACCESSORIES: Power supply

OPTIONS: RK-4PT 19" rack adapter.