



RB-6

6-Channel Power Controller



The RB-6 is a high-performance power supply that distributes power to up to six external units. Four power outlets have on/off push-button control and two power outlets have on/off switching as well as full voltage control.

FEATURES

- **Active Output Control** - All outputs On/Off control, 5 & 6 min/max with full voltage variability via rotary knobs.
- **Power Output** - 10A total, maximum 6A per output.
- **Embedded Web Server Control** - Turns On & Off all channels and adjusts voltage on 5 & 6, schedules outlet activity of each channel separately via Ethernet.
- **Expandable** - Cascades up to 8 units.
- **Varied Control Options** - Front panel buttons, IR remote control, RS-232, RS-485 & Ethernet.
- **Indicators** - Push button LEDs show active output, power and IR status LEDs.
- **Worldwide Power Supply** - 100-240V AC, US and EU models available.
- **Standard 19" Rack Mount Size** - 1U. Rack "ears" included.

TECHNICAL SPECIFICATIONS

| | |
|------------------------|---|
| INPUT: | 1 AC power input. |
| OUTPUTS: | 6 controllable AC power outputs. |
| CONTROL: | Front panel buttons, IR remote control, RS-232 on a 9-pin D-sub connector, RS-485 on a 3-pin terminal block, Ethernet on an RJ-45 connector, embedded Web server. |
| POWER CONSUMPTION: | 100-240V AC, 50/60Hz, 30VA. |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F). |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F). |
| HUMIDITY: | 10% to 90%, RHL non-condensing. |
| DIMENSIONS: | 19" x 9.3" x 1U W, D, H, rack mountable. |
| WEIGHT: | 1.8kg (3.97lbs) approx. |
| INCLUDED ACCESSORIES: | Rack "ears", IR remote control, power cord. |
| OPTIONS: | Remote IR receiver cable Kramer P/N 505-70434010-S. |

