



SL-1

Master Room Controller



The SL-1 is a master room controller. It controls audio components, video components and other room facilities such as lights and screens.

FEATURES

- **2 Bidirectional RS-232 Ports** - Control AV equipment such as projectors, LCD and PDP displays, power amplifiers, switchers and scalars.
- **3 Relay Contact Closure Ports** - Conveniently control other room items related to the AV system such as raising and lowering drapes, the screen or the projector.
- **IR Control** - 1 input (3.5mm) & 2 outputs (terminal blocks).
- **IR Learning Function** - Learns commands from any IR remote.
- **Kramer Site-CTRL™ Compatible** - For network remote control and management using Kramer Site-CTRL software over the Ethernet port.
- **K-NET™ Control Channel** - For connecting compatible user interfaces and supplying power and control data over a single cable.
- **USB Port** - For uploading configuration file.
- **Flexible Control** - Ethernet, K-NET™, IR sensor and external IR commands.

TECHNICAL SPECIFICATIONS

PORTS:	2 RS-232 and 1 K-NET™ on terminal block connectors; 1 Ethernet on an RJ-45 connector; 1 infrared sensor, 1 infrared on a 3.5mm mini jack connector; 1 USB for programming.
OUTPUTS:	2 infrared and 3 relays (36V AC or DC, 2A, 60V AC maximum on non-inductive load) on terminal block connectors.
DEFAULT IP SETTINGS:	IP number – 192.168.1.39; Mask – 255.255.0.0; Gateway – 0.0.0.0.
INDICATORS:	LED indicator for each function.
POWER CONSUMPTION:	12V DC, 2A (from power supply) or 12V DC over K-NET™ connection.
DIMENSIONS:	12cm x 7.2cm x 2.4cm (4.7" x 2.8" x 1.0") W, D, H.
WEIGHT:	0.3kg (0.7lbs).
INCLUDED ACCESSORIES:	Power supply, screwdriver.
OPTIONS:	RK-3T 19" rack adapter, RC-4 remote controller.

