

- Weight Per Single Speaker - 3.4kg (7.05lbs) approx.
- Shipping Weight (Pair) - 9.7kg (21.38lbs) approx.



KRAMER ELECTRONICS, Ltd.

www.kramerelectronics.com

SPK-CC688

Two-Way Closed Ceiling Speakers with 8 inch Back Can



The **SPK-CC688** is a pair of two-way speakers designed to be mounted in the ceiling. They have a closed back design with a 8-inch metal can and aluminum grilles. The dual-driver coaxial speakers are design with transformer and behind-the-grille power selector switch with either direct 8Ω or 70/100 volt room balancing.

- Type - 2- way ceiling speaker with metal closed back can and transformer.
- Woofer - 6.5 inch polypropylene cone woofer.
- Tweeter - 1 inch silk dome tweeter.
- Impedance - 8Ω.
- Metal Back Can - 8 inches deep.
- Transformer - with 8Ω direct, 70 volt, and 100 volt operation.
- Power Selector - Five-position tab selector behind-the-grille.
- Frequency Response - 20Hz – 20kHz.
- Sensitivity - (SPL) 89dB (1 watt @ 1 meter with 1kHz).
- Recommended Power - RMS 50W, 100W max.
- Grille - Aluminum grilles with UV treatment compliance.
- Size - External diameter 25cm (9.84 inches), mounting depth 24.4cm (9.61 inches), cutout diameter 22.1cm (8.7 inches).
- Package - 2 speakers (1 pair), ceiling mounting kit (C-ring & V-rail kit), template and user manual.

- Weight Per Single Speaker - 3.4kg (7.05lbs) approx.
- Shipping Weight (Pair) - 9.7kg (21.38lbs) approx.



KRAMER ELECTRONICS, Ltd.
www.kramerelectronics.com

SPK-CC688

FEATURES

- **Type** - 2- way ceiling speaker with metal closed back can and transformer.
- **Woofers** - 6.5 inch polypropylene cone woofer.
- **Tweeter** - 1 inch silk dome tweeter.
- **Impedance** - 8Ω.
- **Metal Back Can** - 8 inches deep.
- **Transformer** - with 8Ω direct, 70 volt, and 100 volt operation.
- **Power Selector** - Five-position tab selector behind-the-grille.
- **Frequency Response** - 20Hz - 20kHz.
- **Sensitivity** - (SPL) 89dB (1 watt @ 1 meter with 1kHz).
- **Recommended Power** - RMS 50W, 100W max.
- **Grille** - Aluminum grilles with UV treatment compliance.
- **Size** - External diameter 25cm (9.84 inches), mounting depth 24.4cm (9.61 inches), cutout diameter 22.1cm (8.7 inches).
- **Package** - 2 speakers (1 pair), ceiling mounting kit (C-ring & V-rail kit), template and user manual.
- **Weight Per Single Speaker** - 3.4kg (7.05lbs) approx.
- **Shipping Weight (Pair)** - 9.7kg (21.38lbs) approx.