

KRAMER ELECTRONICS, Ltd.

TP-105HD

1:2 Twisted Pair Line Driver & Distribution Amplifier





The TP-105 and TP-105HD are line drivers and distribution amplifiers for twisted pair signals. They take a twisted pair input and distribute it to 2 identical twisted pair outputs.



www.kramerelectronics.com

TP-105HD

FEATURES

- HDTV Compatible (TP-105HD).
- Resolution WUXGA & 1080p (TP-105HD).
- Twisted Pair Output RJ-45 connectors.
- Level (Gain) and EQ (Peaking) Controls.
- System Range Up to 100m (320ft).
- Cable UTP (unshielded twisted pair) or STP (shielded twisted pair) such as CAT 5.
- Power Connect[™] SystemOnly one unit in a system, the transmitter or the receiver needs to be connected to a power source when the devices are within 50m (150ft) of each other.
- Compact Kramer TOOLS[™]3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUT:	1 RJ-45 connector.
OUTPUT:	2 RJ-45 connectors.
MAX OUTPUT LEVEL:	1.6Vpp.
MAX RESOLUTION:	WUXGA & 1080p.
DIFF. GAIN (PAIR):	1.2%.
DIFF. PHASE (PAIR):	0.1Deg.
K-FACTOR (PAIR):	<0.1%.
S/N RATIO (PAIR):	69dB.
CONTROLS:	EQ.: 0 to 4.4dB @50MHz; LEVEL: -5.5dB to 1.4dB.
COUPLING:	AC.
POWER SOURCE:	12V DC, 220mA.
DIMENSIONS:	12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98") W, D, H.
WEIGHT:	0.3kg (0.67lbs) approx.
ACCESSORIES:	Power supply.
OPTIONS:	RK-3T 19" rack adapter.