


The **VM-24HD** is a high-performance distribution amplifier for SDI (SMPTE 259M and 344M) and HD-SDI (SMPTE 292M) and Dual Link HD-SDI (SMPTE 372M) signals. The unit takes two inputs, provides reclocking and equalization, and distributes both signals to four outputs each, or one dual link signal to four identical outputs.



- Max Data Rate – 1.485 Gbps.
- Kramer re-Klocking™ and Equalization Technology – Rebuilds the digital signal to travel longer distances.
- HDTV Compatible.
- Data Rates – 143, 177, 270, 360, 540, 1483.5, and 1485 Mbps.
- Lock, SD, and HD Output Indication LEDs.
- Compact Size – Two units can be rack mounted side-by-side in a 1U rack space with the optional RK-T2B rack adapter.



Rebuilds the digital signal to travel longer distances. HDTV Compatible. Data Rates - 143, 177, 270, 360, 540, 1483.5, and 1485 Mbps. Lock, SD, and HD Output Indication LEDs. Compact Size - Two units can be rack mounted side-by-side in a 1U rack space with the optional RK-T2B rack adapter.

- **INPUTS:** - 2 SMPTE-259M, 292M, 344M serial video, 75Ω on BNC connectors
- **OUTPUTS:** - 8 equalized and reclocked SMPTE-259M, 292M, 344M outputs 75Ω on BNC connectors
- **OUTPUT LEVEL:** - 800mVpp/75Ω
- **MAX. DATA RATE:** - 1.485Gbps
- **COUPLING:** - AC

DIMENSIONS: 18.8cm x 11.4cm x 2.4cm (7.4" x 4.5" x 1.0") W, D, H

WEIGHT: 0.6kg (1.4lbs)

ACCESSORIES: Power supply, mounting brackets

OPTIONS: 19" rack adapters

DIMENSIONS: 12.1cm x 7.2cm x 2.4cm (4.7" x 2.8" x 1.0") W, D, H (VM-22HD); 18.8cm x 11.4cm x 2.4cm (7.4" x 4.5" x 1.0") W, D, H (VM-24HD).

WEIGHT: 0.3kg (0.66lbs) approx (VM-22HD); 0.5kg (1.1lbs) approx (VM-24HD).

ACCESSORIES: Power supply, mounting bracket.

OPTIONS: RK-3T 19" rack adapter (VM-22HD); RK-T2B 19" rack adapter (VM-24HD).