



WP-4iR

Infra-Red Repeater



The WP-4iR is an infrared signal repeater that operates at distances up to 75m (240ft). The unit extends infrared signals into areas where there is no direct line-of-sight for normal infrared signal operation.

FEATURES

- **Outputs** - Up to 4 signals can be distributed to IR Receivers. Optional IR Emitter Cables - C-A35/IRE-10' single emitter (1 included) & C-A35/2IRE-10' dual emitter (Not included). Wall Plate - 1 Gang.
- **Dimensions** - 6.9cm x 2.3cm x 11.4cm (2.71" x 0.91" x 4.49") US; 8.6cm x 2.3cm x 8.6cm (3.39" x 0.91" x 3.39") and 8cm x 2.3cm x 8cm (3.15" x 0.91" x 3.15") EU W, D, H.

TECHNICAL SPECIFICATIONS

POWER 12V DC, 95mA

SOURCE:

DIMENSIONS: USA: 6.9cm x 4.4cm x 11.4cm (2.72" x 1.74" x 4.5", W, D, H) Belgium and Germany: 8cm x 4.4cm x 8cm (3.15" x 1.74" x 3.15", W, D, H) UK and most of Europe: 8.6cm x 3.8cm x 8.6cm (3.39" x 1.74" x 3.39", W, D, H)

WEIGHT: 0.15 kg. (0.55 lbs) approx.

OPTIONS: IR Emitter Control Cable - C-A35/IRE-10' single emitter & C-A35/2IRE-10' dual emitter 3.5mm
EXTENSION CABLES - C-A35M/A35F-50' C-A35M/A35F-65'

ACCESSORIES: Power Supply, 3.5mm to IR Emitter Control Cable (C-A35/IRE-10')

ACCESSORIES: Power Supply, 3.5mm to IR Emitter Control Cable (C-A35/IRE-10')

OPTIONS: IR Emitter Control Cable - C-A35/IRE-10' single emitter & C-A35/2IRE-10' dual emitter 3.5mm
EXTENSION CABLES - C-A35M/A35F-50' C-A35M/A35F-65'