

# Flexible and cost-efficient LCD laser projector

PT-MZ880

New LCD Laser Projectors Deliver Well-Balanced Colour and Brightness with Seamless Integration into Corporate, Education, and Museum Environments

## KEY FEATURES

- Laser LCD, 8 000 lumens, WUXGA
- Compact and lightweight body, designed with ultra-low noise operation (26dB)
- Wide Lens shift area and Ultra-Short Throw lens to expand installation capability
- Edge Blending function to realize versatile space creation
- Significant contribution to sustainability thanks to low Power consumption and Washable Eco Filter

## SPECIFICATIONS

|   |   |
|---|---|
| <b>Projector type</b>   | LCD projectors  |
| <b>LCD panel   Panel size (mm)</b>  | 19.3 mm diagonal (16:10 aspect ratio)   |
| <b>LCD panel   Panel size (inch)</b>                                      | 0.76 inch diagonal (16:10 aspect ratio)   |
| <b>LCD Panel   Display Method</b>   | Transparent LCD panel (x 3, R/G/B)  |
| <b>LCD Panel   Drive Method</b>   | Active matrix   |
| <b>LCD Panel   Pixels</b>   | 2,304,000 ( Pixels 1920 x 1200) pixels x 3  |
| <b>Light Source</b>   | Laser diodes  |
| <b>Light Output*1 *2</b>  | 8,000 lm  |
| <b>Resolution</b>   | WUXGA (1920 x 1200 pixels)  |
| <b>Contrast Ratio*1</b>   | 3,000,000:1 (Full On/Full Off) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1] or [2]. HDMI signal input) |
| <b>Screen size (diagonal) (mm)</b>  | 1.02–10.16 m (40–400 in), 1.52–10.16 m (60–400 in) with the ET-ELW22, 2.54–10.16 m (100–400 in) with the ET-ELU20, 16:10 aspect ratio   |
| <b>Screen size (diagonal) (inch)</b>                                      | 1.02–10.16 m (40–400 in), 1.52–10.16 m (60–400 in) with the ET-ELW22, 2.54–10.16 m (100–400 in) with the ET-ELU20, 16:10 aspect ratio   |
| <b>Center-to-corner zone ratio*1</b>                                      | 85 %  |
| <b>Lens</b>   | Powered zoom (throw ratio 1.61–2.76:1), powered focus F = 1.7–2.3, f = 26.8–45.5 mm (for supplied lens; optional lenses also available) |
| <b>Lens shift   Vertical(From the origin point of the lens mounter)</b>   | ±67 % (powered) (for supplied lens; optional lenses also available*4)   |
| <b>Lens shift   Horizontal(From the origin point of the lens mounter)</b> | ±35 % (powered) (for supplied lens; optional lenses also available*4)   |
| <b>Keystone Correction Range</b>  | Vertical: ±25 °, Horizontal: ±30 ° (for supplied lens; optional lenses also available*4)  |
| <b>Installation</b>   | Ceiling/floor, front/rear, free 360-degree installation   |

|  |  |
|--|--|
| <b>Terminals   HDMI In</b>   | HDMI 19-pin x 3 (Compatible with HDCP 2.3, Deep Color, 4K/60p*5 signal input), CEC supported   |
| <b>Terminals   Computer In</b>                                       | D-sub HD 15-pin (female) x 1 (RGB/YBPBR/YBCBR)   |
| <b>Terminals   Monitor Out</b>                                       | D-sub HD 15-pin (female) x 1 (RGB/YBPBR/YBCBR)   |
| <b>Terminals   Serial / Multi Sync In</b>                            | D-sub 9-pin (female) x 1 for external control/link control (RS-232C compliant)   |
| <b>Terminals   Multi Sync Out</b>                                    | D-sub 9-pin (male) x 1 for link control  |
| <b>Terminals   REMOTE 1 IN</b>                                       | M3 stereo mini-jack x 1 for wired remote control   |
| <b>Terminals   Remote 2 In</b>                                       | D-sub 9-pin (female) x 1 for external control (parallel)   |
| <b>Terminals   Audio In</b>  | M3 stereo mini-jack x 1  |
| <b>Terminals   Audio Out</b>   | M3 stereo mini-jack x 1  |
| <b>Terminals   DIGITAL LINK</b>                                      | RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBaseT™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], Art-Net, HDCP 2.3, Deep Color, 4K/60p*5 *6 signal input)  |
| <b>Terminals   LAN</b>   | RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (Compatible with PLink™ [Class 2], Art-Net)   |
| <b>Terminals   DC Out</b>  | USB Connector (Type A) x 1 (Output 5 V/2 A)  |
| <b>Power Supply</b>  | AC 100–240 V, 50/60 Hz   |
| <b>Power Consumption*7   Maximum power consumption</b>               | 490 W (5.4–2.6 A) (510 VA)<br>(Power consumption is 465 W at 200–240 V)  |
| <b>Power Consumption*7   On-mode power consumption (Light power)</b> | [NORMAL]: 435 W (100–120 V), 415 W (200–240 V)<br>[ECO]: 315 W (100–120 V), 300 W (200–240 V)<br>[QUIET]: 310 W (100–120 V), 295 W (200–240 V)   |
| <b>Cabinet Materials</b>   | Molded plastic   |
| <b>Filter</b>  | Included (Estimated maintenance time: approx. 20,000 hours)  |
| <b>Operation noise*1</b>   | 34 dB (NORMAL/ECO), 27 dB (QUIET)  |
| <b>Dimensions (W x H*8 x D)</b>                                      | 561 x 224 x 439 mm (22 3/32" x 8 13/16" x 17 9/32") (with supplied lens)   |
| <b>Weight*9</b>  | Approx. 18.6 kg (41.0 lbs) (with supplied lens)  |
| <b>Operating Environment</b>   | Operating temperature: 0–45 °C (32–113 °F)*10 operating humidity: 20–80 % (no condensation)  |
| <b>Applicable software/application</b>                               | Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Smart Projector Control for iOS/Android™, Geometry Manager Pro*11   |
| <b>Note</b>  | *1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. *2 When [PICTURE MODE] is set to [DYNAMIC] and [LIGHT POWER] is set to [NORMAL]. *3 Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2]). Estimated time until light output declines to 50 % varies depending on environment. *4 Lens-shift range and keystone correction range may vary depending on lens. *5 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. *6 YBPBR[2]:0 format only for 4K/60p signals input via DIGITAL LINK. *7 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft). *8 With legs at shortest position. *9 Average value. May differ depending on the actual unit. *10 Note that the projector cannot be used at altitudes 2,700 m (8,858 ft) or higher above sea level. In the following operating environments, light output may be reduced to protect the projector: when the projector is used at altitudes below 700 m (2,297 ft) and ambient temperature is 38 °C (100 °F) or higher; when the projector is used at altitudes between 700 m (2,297 ft) and 1,400 m (4,593 ft) exclusive and ambient temperature is 36 °C (97 °F) or higher; when the projector is used at altitudes between 1,400 m (4,593 ft) and 2,100 m (6,890 ft) exclusive and ambient temperature is 34 °C (93 °F) or higher; and when the projector is used at altitudes between 2,100 m (6,890 ft) and 2,700 m (8,858 ft) exclusive and ambient temperature is 32 °C (90 °F) or higher. *11 Some functions available in Geo Pro software are not supported by the PT-MZ880 Series. |

URL: <https://business.panasonic.pl/systemy-wizualne/pt-mz880>

## CONTACT

Web: <https://business.panasonic.pl/systemy-wizualne/contact-us>

