



LOW IMPEDANCE/ MPA4-150R

Multichannel Amplifier

APPLICATIONS

- Public Address
- Theme parks
- Clubs
- Theme restaurants
- Multi-purpose halls
- Boardrooms and conference halls
- Franchise retail shops

MPA4-150R is a 4 x 150 W multichannel amplifier, for high end installations.



MPA4-150R



MPA4-150R

ACCESSORIES



- WPa Series

KEY FEATURES

- 4 analogue audio inputs x 4 powered audio outputs
- Individual input sensitivity controls with sealing possibility to avoid unwanted manipulation
- Signal presence (SP) and CLIP indicators for each channel
- Balanced inputs, XLR connectors (Euroblock in 150W models), Euroblock output connectors
- Stack outputs on all models
- Input channels link switch for superior versatility
- Independent VCA (EUROBLOCK) volume remote control port for each input channel, ready for external 0-10 V signal, compatible with WPa series wall panels
- Noiseless convection cooling (80 and 150 W models)
- Dual Slope Controlled Fan system (MPA4-400R)
- Totally protected against shorting, DC at the outputs and overheating

	MPA4-150R
1 channel @ 4Ω (RMS)	182W
1 channel @ 8Ω (RMS)	116W
All channels @ 4Ω (RMS)	146W
2 bridged channels @ 8Ω (RMS)	370W
Dimensions / Weight	HxWxD: 88 (2RU)x482,6x280mm / 9,3 kg.