# HCS-5300CE/80 Wireless Chairman Unit with Voting and Channel Selection



#### **Features**

- Table, stylish and ergonomic design
- Wireless unit, easy setup and removal
- Hi-Fi loudspeaker
- Priority button
- Pluggable microphone
- System controls up to 1000 contribution units
- 5 voting keys
- Transmitting up to 8 CHs high quality digital audio signals
- Built-in channel selector consists of up/down channel select keys and 2-digit channel indicator display
- Broadcast standard microphone and digital infrared audio processing and transmitting technologies ensure 20 Hz to 20 kHz perfect sound quality, extremely low distortion factor
- Digital infrared transmission technology guarantees privacy, no worries about eavesdropping and radio interference, no radiation, no radio frequency license needed
- Adopts 1~8 MHz transmission frequency, excellent immunity to RF interference from HF-driven lighting and mobile phones
- Microphone sensitivity and EQ individually adjustable
- Built-in rechargeable Lithium battery pack

The stylish and ergonomically designed chairman unit has all the necessary facilities to enable the user to chair a conference. Similar in appearance and function to HCS-5300DE/80 Delegate Unit, the HCS-5300CE/80 Chairman Unit includes an extra microphone priority button. When pressed, the priority button causes all currently active microphones to be switched off temporarily or permanently, allowing the chairman to take control of the meeting. Separate rechargeable Lithium battery packs can be removed and replaced in a matter of seconds, providing maximum flexibility in recharge scheduling.

## **Functions**

- Compliant with IEC 60914
- Based on TAIDEN originated dirATC-digital infrared Audio Transmitting and Control technologies
- Infrared transmitting carrier frequency conforms to IEC 61603-7, DQPSK digital modulation/demodulation technology
- System controls up to 1000 contribution units
- Transmitting up to 8 CHs high quality digital audio signals
- Every delegate unit is assigned an individual ID for convenient setup and to avoid double ID forever
- Broadcast standard microphone and digital infrared audio processing and transmitting technologies ensure 20 Hz to 20 kHz perfect sound quality, extremely low distortion factor
- Digital infrared transmission technology guarantees privacy, no worries about eavesdropping and radio interference, no radiation, no radio frequency license needed
- Adopts 1~8 MHz transmission frequency, excellent immunity to RF interference from HF-driven lighting and mobile phones
- Stem microphone can be unplugged during adjournment, easy to maintain
- Mini-microphone, with foam windshield
- Hi-Fi loudspeaker, minimal feedback
- Ø 3.5 mm stereo headphone jack for headphone with controllable volume
- Microphone On/Off button, 5 voting keys
- Built-in channel selector (operable only when earphone is inserted)
- Microphone sensitivity and EQ individually adjustable
- System implements the following facilities when operated in stand-alone mode:
  - "ACTIVE MICS", set the number of delegates permitted to speak at the same time (1/2/3/4)
  - "OPEN" mode, if Mic. active limit has been reached, next microphone cannot be turned on when pressing "Mic. On/Off" button
  - "OVERRIDE" mode, if Mic. active limit has been reached, when pressing "Mic. On/Off" button, next microphone is turned on and the first active microphone is turned off
  - "VOICE" mode, Mic. sensitivity and close time adjustable, built-in "Flash-on" technology for quick voice control
  - Simultaneous interpretation
- In combination with the corresponding software modules, multiform voting can be implemented:
  - Parliamentary: YES/NO/ABSTAIN
  - Questionnaire: 1/2/3/4/5
  - ◆ Audience response: --/-/0/+/++
- Key-press sign-in
- Automatic video tracking, when cooperating with camera and video switcher unit
- Activatable at any time provided that the total number of active microphones (including the active microphone of the chairman) is within the maximum of 4 active microphones allowed by the system
- Priority button to switch off or to mute the speaking units according to preset
- System supports up to 20 chairman units, while only 1 chairman unit has the control facilities listed above

 Built-in rechargeable Lithium battery operation duration: 14.4 hours when microphone is continuously on; 48 hours when microphone is off

## **Controls and Indicators**

- Graphic 64×48 LCD with back-lighting for displaying channel number, language name, battery capacity and signal icon
- Built-in channel selector consists of up/down channel select keys and 2-digit channel indicator display
- Uni-directional electret condenser microphone with two-color illuminated ring
- Charging indicator
- Fully charged indicator
- Power switch
- Headphone volume control button
- Five voting keys with indicators
- Microphone On/Off button with indicator
- Priority button

## Interconnections

- Socket for pluggable microphone
- Ø 3.5 mm stereo headphone jack
- Power adapter interface

## **Technical Specifications**

## **Electrical**

## **Headphone connection**

Frequency response	20 Hz to 20 kHz (-3dB)
Headphone load impedance	≥16 Ohm × 2
Headphone output	10 mW
Microphone	
Transducer	Electret-condenser
Polar pattern	Uni-directional
Sensitivity	46 dBV/Pa
Frequency response	30 Hz to 20 kHz
Directionality 0°/180°	>20 dB (1 kHz)
Equivalent noise	20 dBA (SPL)
Max.SPL	125 dB (THD<3%)
Interface data	
	~~
Connector ©	3.5 mm stereo jack for headphone
Operation time of battery pack	
Operation time of battery pack	
Operation time of battery pack When mic. is continuously on	k
Operation time of battery pack When mic. is continuously on	kApprox. 14.4 hours
Operation time of battery pack When mic. is continuously on	kApprox. 14.4 hours
Operation time of battery pack When mic. is continuously on When mic. is off  Mechanical	Approx. 14.4 hours Approx. 48 hours
Operation time of battery pack When mic. is continuously on When mic. is off  Mechanical Mounting	kApprox. 14.4 hours
Operation time of battery pack When mic. is continuously on When mic. is off  Mechanical Mounting	Approx. 14.4 hours Approx. 48 hours Tabletop
Operation time of battery pack When mic. is continuously on When mic. is off  Mechanical Mounting Dimensions (h x w x d) (w/o Mic Weight	Approx. 14.4 hours Approx. 48 hours Tabletop
Operation time of battery pack When mic. is continuously on When mic. is off  Mechanical Mounting Dimensions (h x w x d) (w/o Mic Weight Excl. battery	Approx. 14.4 hours Approx. 48 hours Tabletop )73 x 184 x 134 mm

Color\_\_\_\_\_Silver (PANTONE 428C) / Charcoal

gray (PANTONE Cool Gray 11C)

# **Ordering Information**

HCS-5300CE\_S/80\_\_\_\_\_\_Digital IR Wireless Chairman Unit
(discussion, voting, 1+7 CHs,
silver, excl. battery)

HCS-5300CE\_G/80\_\_\_\_\_Digital IR Wireless Chairman Unit
(discussion, voting, 1+7 CHs,
charcoal gray, excl. battery)