

HCS-5302C/80 Wireless Chairman Unit



Features

- **Table, stylish and ergonomic design**
- **Wireless unit, easy setup and removal**
- **Hi-Fi loudspeaker**
- **Priority button**
- **Pluggable microphone**
- **System controls up to 1000 contribution units**
- **Broadcast standard microphone and digital infrared audio processing and transmitting technologies ensure 20 Hz to 20 kHz perfect sound quality, extremely low distortion factor**
- **Digital infrared transmission technology guarantees privacy, no worries about eavesdropping and radio interference, no radiation, no radio frequency license needed**
- **Excellent immunity to RF interference from HF-driven lighting and mobile phones**
- **Microphone sensitivity and EQ individually adjustable**
- **Built-in rechargeable Lithium battery pack**

The stylish and ergonomically designed chairman unit has all the necessary facilities to enable the user to chair a conference. Similar in appearance and function to HCS-5302D Delegate Unit, the HCS-5302C Chairman Unit includes an extra microphone priority button. When pressed, the priority button causes all currently active microphones to be switched off temporarily or permanently, allowing the chairman to take control of the meeting. Separate rechargeable Lithium battery packs can be removed and replaced in a matter of seconds, providing maximum flexibility in recharge scheduling.

Functions

- Compliant with IEC 60914
- Based on TAIDEN originated dirATC-digital infrared Audio Transmitting and Control technologies
- Infrared transmitting carrier frequency conforms to IEC 61603-7, DQPSK digital modulation/demodulation technology
- System controls up to 1000 contribution units
- Every delegate unit is assigned an individual ID for convenient setup and to avoid double ID forever
- Broadcast standard microphone and digital infrared audio processing and transmitting technologies ensure 20 Hz to 20 kHz perfect sound quality, extremely low distortion factor
- Digital infrared transmission technology guarantees privacy, no worries about eavesdropping and radio interference, no radiation, no radio frequency license needed
- Excellent immunity to RF interference from HF-driven light and mobile phones
- Stem microphone can be unplugged during adjournment, easy to maintain
- Mini-microphone, with foam windshield
- Hi-Fi loudspeaker, minimal feedback
- Ø 3.5 mm stereo headphone jack for headphone with controllable volume
- Microphone On/Off button
- Microphone sensitivity and EQ individually adjustable
- System implements the following facilities when operated in stand-alone mode:
 - ◆ "ACTIVE MICS", set the number of delegates permitted to speak at the same time (1/2/3/4)
 - ◆ "OPEN" mode, if Mic. active limit has been reached, next microphone cannot be turned on when pressing "Mic. On/Off" button
 - ◆ "OVERRIDE" mode, if Mic. active limit has been reached, when pressing "Mic. On/Off" button, next microphone is turned on and the first active microphone is turned off
 - ◆ "VOICE" mode, Mic. sensitivity and close time adjustable, built-in "Flash-on" technology for quick voice control
- Automatic video tracking, when cooperating with camera and video switcher unit
- Activatable at any time provided that the total number of active microphones (including the active microphone of the chairman) is within the maximum of 4 active microphones allowed by the system
- Priority button to switch off or to mute the speaking units according to preset
- System supports up to 20 chairman units, while only 1 chairman unit has the control facilities listed above
- Built-in rechargeable Lithium battery operation duration: 14.4 hours when microphone is continuously on; 48 hours when microphone is off

Controls and Indicators

- Graphic 64×48 LCD with back-lighting for displaying battery capacity and signal icon
- Uni-directional electret condenser microphone with two-color illuminated ring
- Charging indicator
- Fully charged indicator
- Power switch
- Headphone volume control button
- Microphone On/Off button with indicator
- Priority button

Interconnections

- Socket for pluggable microphone
- Ø 3.5 mm stereo headphone jack
- Power adapter interface

Ordering Information

- HCS-5302C_S/80Digital IR Wireless Chairman Unit
(discussion, silver, excl. battery)
- HCS-5302C_G/80Digital IR Wireless Chairman Unit
(discussion, charcoal gray, excl. battery)

Technical Specifications

Electrical

Headphone connection

Frequency response.....20 Hz to 20 kHz (-3dB)
 Headphone load impedance.....≥16 Ohm × 2
 Headphone output.....10 mW

Microphone

Transducer.....Electret-condenser
 Polar pattern.....Uni-directional
 Sensitivity.....-46 dBV/Pa
 Frequency response.....30 Hz to 20 kHz
 Directionality 0°/180°.....>20 dB (1 kHz)
 Equivalent noise.....20 dBA (SPL)
 Max.SPL.....125 dB (THD<3%)

Interface data

Connector.....Ø 3.5 mm stereo jack for headphone

Operation time of battery pack

When mic. is continuously on.....Approx. 14.4 hours
 When mic. is off.....Approx. 48 hours

Mechanical

Mounting.....Tabletop
 Dimensions (h x w x d) (w/o Mic.).....73 x 184 x 134 mm
 Weight
 Excl. battery.....0.5 kg
 Incl. battery.....0.8 kg
 ColorSilver (PANTONE 428C) / Charcoal gray (PANTONE Cool Gray 11C)