

HCS-8300KMX2 Congress Gigabit Network Switcher



Functions

- Based on TAIDEN originated GMC-STREAM Gigabit Multimedia Congress Stream technology
- Sync power on/off with the Congress Main Unit
- Built-in PoE switch to choose way of power supply:
 - ON: connecting DELEGATE port to tabletop congress terminals or the Distributor HCS-8368T/50 for power supply and transmission of control data and multimedia data
 - OFF: DELEGATE port supporting daisy-chain connection to HCS-8368/50 Series Paperless Multimedia Congress Terminal with power supply via 3 2P aviation plugs

Interconnections

- 1 × RJ45 standard port for connection with Ethernet switcher
- 5 × RJ45 standard port for connection with HCS-8368/50 Series Paperless Multimedia Congress Terminal (via Cat.5e/Cat.6 cable)
- 2 × 6P-DIN interface for connection with the Congress Main Unit or cascading to another HCS-8300KMX2 (equipped with CBL6PP-01 - 1-meter 6-pin extension cable with two plugs)
- 3 × 2P aviation plug for supplying power to HCS-8368/50 series Multimedia Congress Terminal (equipped with CBL4PK-01 - 1-meter power adapter cable)

Technical Specifications

Electrical

Power supply.....AC 100 V - 240 V, 50 Hz / 60 Hz
 Power output.....Four power outputs, each output 48V DC, 3A
 Power consumption.....350 W

Mechanical

Mounting.....Tabletop or mounted in a 19" rack
 Dimensions (h x w x d).....43 × 483 × 208 mm
 (1U high, full rack width)
 Weight.....3.6 kg
 Color.....Gray (PANTONE 425 C)

Ordering Information

HCS-8300KMX2.....Congress Gigabit Network Switcher
 (for G3 multimedia congress terminal)

HCS-8300POE Congress PoE Network Switcher



Functions

- Sync power on/off with the Congress Main Unit
- Built-in PoE switch to choose way of power supply:
 - ON: connecting DELEGATE port to tabletop congress terminals or the Distributor HCS-8368T/50 for power supply and transmission of conference data

Interconnections

- 1 × RJ45 standard port (ETHERNET) for connection with CMU or EMU
- 5 × RJ45 standard port for connection with HCS-8665 Series Multimedia Congress Terminal (via Cat.5e/Cat.6 cable)
- 2 × 6P-DIN interface for connection with the Congress Main Unit or cascading to another HCS-8300PoE (equipped with CBL6PP-01 - 1-meter 6-pin extension cable with two plugs)

Technical Specifications

Electrical

Power supply.....AC 100 V - 240 V, 50 Hz / 60 Hz
 Control port.....5 × RJ45 socket with power supply
 Power consumption.....350 W

Mechanical

Mounting.....Tabletop or mounted in a 19" rack
 Dimensions (h x w x d).....43 × 483 × 208 mm
 (1U high, full rack width)
 Weight.....3.6 kg
 Color.....Gray (PANTONE 425 C)

Ordering Information

HCS-8300POE.....Congress PoE Network Switcher
 (supports PoE, for HCS-8665 series multimedia congress terminal)