

## HCS-8685BM Booth Manager




---

### Functions

- An ideal solution for booth allocation, allowing allocating booths at will without changing existing wiring
- 1x RJ45 port, for LAN connection
- 2x8P-DIN ports, can connect up to 6 interpreter units
- Back-lit 132x32 LCD display, showing IP address of the Booth Manager and the number of the booth where it is located
- Web control facility, allows for access and complete configuration via web page
- Allocation of the Booth Manager to a certain HCS-8600 series conference system via HCS-8544S Booth Allocation and Management Software
- Integrated Type-C USB interface for system upgrading. Convenient for system maintenance

### Controls and Indicators

- 132x32 LCD with back-lighting display
- Power switch with indicator

### Interconnections

- 2 x 8P-DIN interface for connection with interpreter units
- 1 x RJ45 standard socket for connection to LAN
- Type-C USB interfaces for system upgrading

---

### Technical Specifications

#### Electrical

Power supply.....DC 48 V, 1.875 A  
 Power consumption.....4 W

#### Mechanical

Dimensions (h x w x d).....46 x 190 x 134 mm  
 Weight.....1.5 kg  
 Color.....Black (PANTONE 419 C)

---

### Ordering Information

HCS-8685BM.....Booth Manager (2 outlets for interpreter units)