



CSW55

Quick fit 5 1/4" evacuation ceiling speaker 100V

The CSW55 is a professional ceiling speaker with an integrated white LED unit which can be used as visible alarm signal. It features a 4 1/3" single cone loudspeaker which is capable of producing up to 10 Watt RMS, with a maximum of 20 Watt and it ensures good reproduction of speech and background music in all situations. The speaker is fitted with a 100V line transformer and there are different power taps available for 6 Watt, 3 Watt and 1.5 Watt at 100V. The integrated White unit deliver a light intensity of 24 Lumen on a supply voltage of 24V DC.



Impedance:



Voltage:



System specifications:

Speaker type		Broadband
RMS Power		15 W
Impedance		8 Ω
Line Transformer Tappings	1	6 W / 1600 Ω
	2	3 W / 3300 Ω
	3	1.5 W / 6600 Ω
Sensitivity (1W/1m)		90 dB
Sound Pressure (Max. W/1m)		100.8 dB
Frequency	Response (\pm 3 dB)	70 Hz - 14 kHz
Signal LED	Power	24 V DC
	Current	45 mA
	Angle	120°
	Light Density	24 Lumen
	Colours	White

Product Features:

Dimensions		200 mm (\emptyset)
Weight		0.900 kg
Built-in depth		70 mm
Cut-out measurement		167 mm (\emptyset)
Colours		White (NCS S 1000-N)
Accessories	Optional	Paintable in RAL colours