



PX115_O

High-power outdoor speaker 15"

The PX series are compact full-range loudspeaker cabinets for a wide variety of indoor or outdoor applications. They come in four different models, each of them with different size and performance meeting the requirements for every specific application. The PX115 is the 15" model of the PX family, consisting of a 15" high output woofer and a compression driver with 1.3" voice coil. The compression driver is fitted with a 90° x 75° coverage horn which can be rotated allowing both horizontal and vertical use.

Thanks to the high-quality components and an accurately optimized integrated passive crossover network with tweeter overload protection, the PX115 delivers a clear and natural sound with an RMS power of 300 Watt and a maximum power of 600 Watt. The frequency range (-10 dB) starts from 45 Hz up to 20 kHz and the sensitivity (1W / 1m) reaches 100 dB while a maximum continuous sound pressure level from 125 dB can be achieved.

The construction of the outdoor cabinets is made of dense plywood treated with a special weatherproof surface finish. After this treatment the cabinets are painted with UV resistant high-quality paint the withstand summer heat. The front side of the cabinet is finished with a powder-coated steel grill fixed in place by anti-rust inox screws. Recessed carry handles on both sides of the cabinet make carrying easy.

Positioning and suspension of the speaker are easily achieved by using the standard 35 mm pole adapter on the bottom side and M10 rigging points. An optional mounting bracket provides a complete solution for wall mounting. Two speaker connectors on the rear side of the cabinet provide reliable connections with easy link-through to other cabinets.

Applications:

- Events
- Concert venues
- Clubs, discotheques
- Live performances



Properties:



Rotatable

Impedance:



8 Ohm

System specifications:

Speaker type		2-way
Max. Power		600 W
RMS Power		300 W
Impedance		8 Ω
Sensitivity (1W/1m)		100 dB
Sound Pressure (Max. W/1m)		125 dB
Frequency	Response (\pm 3 dB)	60 Hz - 19 kHz
	Range (-10 dB)	45 Hz - 20 kHz
Crossover	Frequency	2 kHz
	Type	Passive built-in
Dispersion	Horizontal	90°
	Vertical	75°
Connectors		2 x Speakon compatible (Linkthrough)
Drivers	HF	1.3" Compression driver
	MF	15"

Product Features:


Dimensions		435 x 764 x 495 mm (W x H x D)
Weight		35 kg
Construction		Plywood with textured EPDM coating
Front finish		Powder coated steel grill with lining
Mounting & handling	Rigging points	8 x M10
	Stand fitting	35 mm pole adapter on bottom
		M10 screw flange on top
	Carry handles	On both sides
Colours		Black
Accessories	Optional	CPB115P Protective cover bag
		MBK115 Wall mounting bracket

Variants:

- PX115MK2/OB - Outdoor black version

Architects' and Engineers' Specifications:

The loudspeaker cabinet must be a 15" 2-way system. The cabinet must be constructed of high-density plywood with a durable scratch-proof UV resistant coating. The front side must be finished with a powder-coated steel grill which is lined with an acoustically transparent backing, attached with Inox screw. The cabinet must have recessed carry handles on both sides of the cabinet for easy handling, while a standard 35 mm pole adapter and 8 x M10 rigging points must be provided for positioning and suspension of the speaker. The loudspeaker cabinet must have an RMS power handling of 300 Watt with a maximum power handling of 600 Watt. The frequency response (-10 dB) must range from 45 Hz to 20 kHz. The sensitivity must be 100 dB when measured with an input signal of 1 Watt at a distance of 1 meter, while the maximum continuous sound pressure level must reach 125 dB. The loudspeaker must consist of a 1.3" HF compression driver and a 15" medium frequency range loudspeaker. It must have an impedance of 8 Ohm and contain a passive built-in crossover network with a crossover frequency of 2.0 kHz. The complete model is constructed of high-quality components. It must also have an integrated tweeter overload protection circuit. The horn mounted on the HF driver must have a horizontal dispersion of 90° and vertical dispersion of 75° and must be rotatable, allowing both horizontal and vertical use. Connections with the speaker must be made using 2 x Speakon compatible connectors, allowing easy connection and link-through. The loudspeaker cabinet must not exceed a width of 435 mm, a height of 764 mm and a depth of 495 mm.



<p>PX115</p>	<p>Product description: LOUDSPEAKER CABINET 15" 2-WAY 300W RMS</p>
<p>Weight: 35 kg</p>	<p>Outer dimensions: (w x h x d) 435 x 764 x 495</p>
<p>Unit height: N/A</p>	