

## **PMR 60T**

### TWO-WAY PENDANT MONITOR SPEAKER



#### Description

PMR 60T is a two-way pendant monitor speaker, suitable for a wide range of applications. Thanks to its elegant and discreet design and refined finishes, it is suitable for all environmental and architectural conditions. Featuring a 6.5" woofer and 80 W RMS power, it is also equipped with a transformer for connection to constant voltage lines (70/100 V). The high quality of its transducers (arranged in a coaxial configuration) guarantees faithful and precise musical reproduction throughout the audio spectrum and allows to reach truly remarkable sound pressure levels for such compact products. The connection is simple and safe thanks to the removable four-pole screw terminals. The front grille is fixed by magnets and can therefore be easily removed to access the power rotary switch.

#### **Features**

- > 80W RMS power handling
- > 114 dB max SPL
- > 70 ÷ 20000 Hz frequency range
- > 130° constant directivity conical coverage angle
- > 6.5" high power woofer
- > 1" neodymium dome tweeter
- > Self extinguishing plastic body
- > Steel magnetic front grille
- > 4 pole EUROBLOCK connector (audio input and parallel link output)
- > 5 m hanging cable included

#### **Part Number**

13100098 PMR 60T W 13100100 PMR 60T B White - RAL 9003 EAN 8024530020606 Black - RAL 9005 EAN 8024530020590



# **PMR 60T**

## TWO-WAY PENDANT MONITOR SPEAKER

#### Line Art 2D













#### **TECHNICAL SPECIFICATIONS**

**Acoustical specifications** 

Power section

Frequency Response (-10dB) 70 Hz ÷ 20000 Hz

Max SPL @ Im114 dBCoverage angle130°System Sensitivity89 dBAmplificationFull RangeNominal Impedance8 ohm

Nominal Impedance 8 ohm
Power Handling 80 W RMS
Peak Power Handling 320 W PEAK
Crossover Frequencies 2500 Hz

 Transducers
 Dome Tweeter
 1 x 1.0" neo, 1.0" v.c

 Woofer
 1 x 6.5", 1.2" v.c

Input/Output sectionInput connectorsEuroblockOutput connectorsEuroblock

Constant Voltage Transformer 70/100 V

Power selection 1 80 W - 125 ohm

Power selection 2 40 W - 250 ohm

Power selection 3 20 W - 500 ohm

Power selection 4 10 W - 1000 ohm

Power selection 5 5 W - 2000 ohm

Standard complianceSafety agencyCE compliantPhysical specificationsCabinet/Case MaterialABS

Grille Steel
Color White - RAL 9003, Black - RAL 9005

Size / Weight Height 236 mm / 9.29 inches

 $\begin{array}{lll} \mbox{Height} & 236 \mbox{ mm} \slash \mbox{9.29 inches} \\ \mbox{Diameter} & 300 \mbox{ mm} \slash \mbox{11.81 inches} \\ \mbox{Weight} & 5.1 \mbox{ kg} \slash \mbox{11.24 lbs} \end{array}$ 

Technical Specifications Page 2 of 2