

# PREZONE2

Stereo pre-amplifier with 2 stereo source & volume zones



The Apart PREZONE2, a multi-functional stereo preamplifier that allows you to independently control the music source selection and volume in 2 stereo zones. It gives you the possibility to mix the 2 microphone levels easily with one of the 4 music sources.

The innovative and extremely intuitive design of the front panel will instantly indicate how to operate the progressive PREZONE2. The logical rear panel will give every installer an instant understanding on how to install the unit. It's easy to distinguish the PREZONE2 from its competitors. Its higher signal to noise ratio, ease-of-use, logical design and versatile installer features makes it suitable for almost every professional audio application.

## TECHNICAL SPECIFICATIONS

19" (483 mm wide) rack mounting	yes	height- rack units (1U=44 mm) in U	2 U
power supply	100 - 240 VAC	zone outputs	2 stereo
SPDIF output	no	music level control	yes
MIC level control	yes	VCA level control	no
source selection per zone	yes	MIC inputs balanced	2
inputs with Phantom power	2	Phantom power voltage in volts	48
noise gate on MIC	no	selectable input dynamics	no
selectable output dynamics	no	line input balanced	1
line input unbalanced	4	line input SPDIF	no
tone control	yes	RS232 (serial communication port)	yes
wall panel controls	yes	priority input contact	yes
VOX mute	yes	chime	yes
emergency input	yes	priority output contact	yes
priority levels	4	frequency response (in Hz)	20 - 25 k
applicable in 100V	yes	applicable low impedance	yes
Net weight product (kg)	4		

MORE PICTURES



ACCESSORIES



**MICPAT-D**

All call dynamic paging microphone



**MICPAT-2**

Selective 2-zone paging station



**DIWAC**

Digital programmable wall control for  
AC12.8/AUDIOSYSTEM8.8



**D-DIWAC**

Digital wall control Decora Style



**D-ALINP**

Active local input panel Decora style



**ALINP**

Active local input panel