

DIMIC1

All call digital paging station for AUDIOCONTROL12.8



DIMIC1 is an all call digital paging station for use with AUDIOCONTROL12.8 that is easy to configure via the host's graphical installer interface.

In most applications an all call microphone is indispensable to guarantee a good communication. The DIMIC1 microphone is especially designed to function in a plug and play way with our electronics and makes sure that your message will be heard loud and clear throughout the entire office.

DIMIC1 combines an inconspicuous and elegant design with a remarkable sound quality. It has speech-optimized sound processing and a unidirectional condenser microphone.

The unit has Universal configuration of push buttons, an all zone selection button and a push-to-talk button and multicolor paging status LED's.

TECHNICAL SPECIFICATIONS

width in mm	110	depth in mm	240
height in mm	58	weight in gr	600
cut-out dimension in mm	85 x 230	active	Yes
polar pattern	uni-directional	buttons	all zone selection button
indicator	tri-color status	nominal output level	775mV variable balanced
frequency range	220 Hz - 20 kHz	lo-cut	220 Hz, 6dB/oct
power type	Phantom or external power supply	external power supply	12 - 24Vdc/75mA
mic stem length in mm	395	cable length in m	5
connector	RJ45	cable type	CAT5
supported main unit	AUDIOCONTROL12.8	Net weight product (kg)	0,60

MORE PICTURES



ACCESSORIES**RJ45SPLIT**

RJ45 Splitter : 1input, 4 output (MICPAT-4 or ZONE4R)