

Samsung DB22D-T display

Encourage customer engagement with an interactive touchscreen



Highlights

- Experience the advantages of a highly-reliable professional-grade display backed by 3-year warranty.
- Boost power and functionality with the 2nd Generation Samsung SMART Signage Platform (SSSP)
- Project crisp, clear images with FHD output
- Engage viewers with an interactive touchscreen
- Simplify networking with a built-in Wi-Fi module
- Leverage the advantages of the global Samsung brand identity
- Gain flexibility with a compact, 21.5" screen size

Rely on the dependability of Samsung professional-grade displays

Unlike consumer electronics which often results in shorter equipment life spans and malfunctions, Samsung small-sized displays are designed to withstand the rigorous work hours of a commercial environment. In addition, Samsung small-sized displays deliver effective messaging for your business with touchscreen capabilities.

Encourage customer engagement with an interactive touchscreen

The Samsung DB22D-T model takes customer engagement to the next level with 10-point and 2-drawing touch capabilities made possible by the processor's SoC technology. The touch feature further personalizes the experience and encourages interaction with the product or service being offered.

Empower with 2nd Generation SSSP and Samsung's respected branding

Experience unparalleled performance with Samsung's industry-leading 2nd Generation SSSP and powerful quad-core processor with SoC technology. Plus, eliminate the need for a separate PC or media player with the included MagicInfo Player S2 all-in-one, embedded content management solution.

The technological power of the DB22D-P is backed by Samsung's reputation for engineering reliable, cutting-edge digital signage. Its leadership in the industry has made it a global powerhouse in serving the B2B industry and a name that is trusted worldwide.



Samsung DB22D-T display

Specifications

		DB22D-T	
Panel	Diagonal Size	21.5"	
	Type	60 Hz E-LED BLU	
	Resolution	1,920 x 1,080	
	Pixel Pitch (mm/in.)	0.2482 x 0.2482 (0.009 x 0.009)	
	Active Display Area (mm/in.)	476.64 x 268.11 (18.7 x 10.5)	
	Brightness (Typ.)	220 nit	
	Contrast Ratio (Typ.)	1,000:1	
	Viewing Angle (H/V)	178 / 178	
	Response Time (G-to-G)	14 ms	
	Display Colors	16.7 M	
	Color Gamut	72%	
Display	Dynamic C/R	50,000:1	
	H-Scanning Frequency	30 ~ 81 KHz	
	V-Scanning Frequency	48 ~ 75 Hz	
	Maximum Pixel Frequency	148.5 MHz	
Sound	Speaker Type	Built-In Speaker (1 W x 2)	
Connectivity	Input	RGB	Analog D-SUB
		VIDEO	HDMI1
		AUDIO	Stereo mini Jack
	External Control	RS232C(in) thru stereo jack, RJ45	
IO Ports	USB 2.0		
Power	Type	Internal	
	Power Supply	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	
	Power Consumption	Max [W/h], Typical [W/h]	44, 40
		BTU (Max)	150.04
		Sleep mode	less than 0.5 W
Off mode	less than 0.5 W		
Mechanical Spec	Dimension (mm/in.)	Set	507.5 x 311.2 x 59.3 (19.9 x 12.2 x 2.3)
		Package	570 x 376 x 128 (22.4 x 14.8 x 5)
	Weight (kg/lb)	Set	4.4 (9.7)
		Package	5.7 (12.5)
	VESA Mount (mm)	100 x 100	
Bezel Width (mm/in.)	TBD		
Operation	Operating Temperature	0 ~ 40 °C	
	Humidity	10~80%	
Feature	Key	Slim & Light SMART Signage with Built-in MagicInfo Player S2	
	Special	H/W	Temperature Sensor, Pivot Display, Image Rotation, Button Lock, Clock Battery (80 hrs Clock Keeping), Built-In Speaker, WiFi Module Embedded, Touch (10 Point, 2 Drawing)
		S/W	Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play (DDC2B), PIP/PBP, Smart Scheduling, Smart F/W update, Built-In MagicInfo Player S2
	Internal Player (Embedded H/W)	Processor	Cortex-A9 1 GHz Quad Core CPU
Storage (FDM)		4 GB (2 GB occupied by O/S, 2 GB available)	
Certification	Safety	CUL, TUV, CB, EK, PSB, GOST, SIQ, PCBC, NOM, IRAM, SASO, BIS	
	EMC	FCC, CE, VCCI, KCC, BSMI, C-Tick, CCC	
Accessories	Included	Quick Setup Guide, Warranty Card, D-Sub cable, Power Cord, Remote Controller, Batteries	