EB-L1490U



DATASHEET / BROCHURE



































Powerful 9,000-lumen WUXGA 3LCD laser projector offering outstanding image sharpness and brightness, and long-lasting, low maintenance performance.

The EB-L1490U installation laser projector offers powerful 9,000-lumen WUXGA performance with rich, vivid colours, for large rooms and venues, as well as reliable fit and forget performance. With flexible installation and low maintenance, this 4K-enhanced projector offers a perfect solution for scenarios where only maximum performance and durability will do.

Laser-sharp images

Ensure that your presentations, images and videos pack a punch with the vivid, sharp projection offered by this 3LCD laser projector. Designed for larger venues, its high resolution WUXGA images are vivid and bright, even in daylight, while inorganic phosphor wheel technology provides superior light and heat resistance to deliver excellent reliability.

4K enhancement

For a next-level viewing experience, the projector features ingenious 4K enhancement technology, giving images exceptional sharpness and clarity, and ensuring that text in presentations is clearly legible.

Flexible positioning

Thanks to a wide range of motorised lenses, including optional ultra-short-throw (UST) lens, the projector benefits from true 360° installation flexibility, allowing it to be placed virtually anywhere - without loss of brightness or distortion of image. The projector also has a built-in camera to ensure accurate calibration and capture diagnostic images (this can be fully disabled to prevent remote access).

Versatile software

Epson Professional Projector Tool software allows you to set up multi-projector installations straight out of the box, simply and quickly, as well as using advanced techniques such as projection-mapping and edge-blending.

KEY FEATURES

- Laser light source technology Outstanding brightness and colour, with fit-and-forget reliability
- HD images with 4K enhancement Exceptional sharpness, clarity and detail for crisp images and legible text
- Versatile new software Set up multiple projector installations and use advanced projection techniques
- Flexible 360° installation True flexibility without distortion or loss of brightness
- Added peace of mind Product comes with five-year, 20,000hour warranty





PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology LCD Panel 1.03 inch with C2 Fine

IMAGE

Colour Light Output 9,000 lumen- 6,300 lumen (economy) in accordance with IDMS15.4

White Light Output 9,000 lumen - 6,300 lumen (economy) in accordance with ISO 21118:2012

Resolution WUXGA, 1920 x 1200, 16:10

 High Definition
 4K enhancement

 Contrast Ratio
 2,500,000:1

 Native Contrast
 2,000:1

 Light source
 Laser

 Portrait Colour Light Output
 9,000 lm

 Portrait White Light Output
 9,000 lm

Keystone Correction Manual vertical: \pm 45 °, Manual horizontal \pm 30 °

Colour Reproduction upto 1.07 billion colours

OPTICAL

Projection Ratio 1.57 - 2.56:1

Zoom Motorized, Factor: 1 - 1.6

Lens Shift Motorized - Vertical ± 60 %, horizontal ± 18 %

Lens position memory 10 positions

Image Size 60 inches - 1,000 inches

Projection Distance Wide 2 m - 17.2 m

Projection Distance Tele 3.3 m - 27.8 m

Projection Distance Wide/Tele 1.99 m - 27.77 m

Projection Lens F Number 1.8 - 2.5

CONNECTIVITY

Interfaces Stereo mini jack audio in (3x), Stereo mini jack audio out, HDBaseT, BNC in, HDMI in, DVI in,

VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B

(Service Only), HD-SDI, Wireless LAN b/g/n (2.4GHz) (optional)

GENERAL

Energy Use 626 W, 512 W (economy), 0.3 W (standby), On mode power consumption as defined in JBMS-

84 554 W

Heat Dissipation 2,128 BTU/hour (max)
Supply Voltage AC 100 V - 240 V, 50 Hz - 60 Hz

Product dimensions 586 x 492 x 211 mm (Width x Depth x Height)

Product weight 23.7 kg

Noise Level Normal: 37 dB (A) - Economy: 30 dB (A) (4K enhancement OFF)

Temperature Storage -10° C - 60° C

Humidity Operation 20% - 80%, Storage 10% - 90%

Colour White

OTHER

Warranty 60 months Carry in or 20,000 h

EB-L1490U

WHAT'S IN THE BOX

- Remote control incl. batteries
- Quick Start Guide
- Power and signal cable (3 m)
- VGA cable
- Cable cover
- CD Manual



OPTIONAL ACCESSORIES

HDBaseT Transmitter - ELPHD01

V12H547041

• 3D Polarizer - ELPPL01

V12H618A01

• Wireless LAN Adapter - ELPAP10

V12H731P01

• Air Filter - ELPAF51

V13H134A51

• Ceiling Mount - ELPMB47 Low EB-G7000/L1000

V12H802010

• Ceiling Mount - ELPMB48 High EB-G7000/L1000

V12H803010

• Stacking Frame - ELPMB50 - L1000 Series (Premium)

V12H003B50

OPTIONAL LENSES

 Lens - ELPLU03 - G7000 & L1000 Series ST off axis 1 V12H004U03

 Lens - ELPLU04 - G7000 & L1000 Series ST off axis 2 V12H004U04

 Lens - ELPLW05 - G7000 & L1000 Series wide zoom 1 V12H004W05

 Lens - ELPLW06 - L1500U/1505U wide zoom 2 V12H004W06

 Lens - ELPLL08 - Long throw - G7000/L1000 series V12H004L08

 Lens - ELPLM10 - Mid throw 3 - G7000/L1000 series V12H004M0A

 Lens - ELPLM11 - Mid throw 4 - G7000/L1000 series V12H004M0B

 Lens - ELPLM15 - Mid Throw L1500/L1700 Series V12H004M0F

 Lens - ELPLX02 - UST Lens L1500/1700 Series V12H004X02

 Lens - ELPLW08 - Wide throw V12H004W08

LOGISTICS INFORMATION

SKU	V11HA16040
EAN code	8715946671482
Country of Origin	China

For more information please contact:

Home users: 0343 90 37766 Business users*: 0871 42 37766 Republic of Ireland: 01 436 7742 Or visit us at https://www.epson.co.uk/contactus * 10p per minute plus network extras. Web: www.epson.co.uk www.epson.ie



EB-L1490U